

HORIZON SQUARE LOUVRE

LED


CFL



White
HS3/W



Titanium
HS3/X



| Size | HS3 |
|------|-------|
| A | 330mm |
| B | 122mm |

LED / Lamp Types

- 28W & 38W 4-Pin, 3500K, GR10 Cap.
- 16W 2D 4-Pin, 3500K, GR8 Cap.
- LED options
 - White (standard).
 - Warm white (opal).

Materials

- Body: 330mm vandal resistant polycarbonate selfextinguishing fire properties in black / white / titanium.
- Diffuser: Vandal resistant polycarbonate in opal with self-extinguishing fire properties.

Installation

- Wall or ceiling mount.
- BESA fixing and rear cable entry, 3 way mains terminal block, 4 way terminal block for emergency versions & photocell.
- Screw down lid.
- Photocell external use only.

Standards

- IP65.
- IK10.
- 'F' Mark.
- CE.
- BS EN 60598.
- Class I.

Options

| LED | Horizon Square Louvre Code | Colour Finish | Diffuser | IP Rating | CRI | CCT | System Power | Delivered Lumens | Efficacy | Emergency | Photocell |
|----------|----------------------------|---------------|--------------|-----------|-----------|-----------|--------------|------------------|----------|-----------|-----------|
| LED 1800 | HS3/BLL4LED1800 | Black | Premium Opal | IP65 | 80 | 4000K | 16.8W | 764lm | 45.4lm/W | ✓ | ✓ |
| CFL | Horizon Square Louvre Code | Colour Finish | Diffuser | IP Rating | Emergency | Photocell | | | | | |
| 16W HF | HS3/BLL516U6 | Black | Premium Opal | IP65 | ✓ | ✓ | | | | | |
| 28W HF | HS3/BLL528U6 | Black | Premium Opal | IP65 | ✓ | ✓ | | | | | |
| 38W HF | HS3/BLL538U6 | Black | Premium Opal | IP65 | ✓ | ✓ | | | | | |

Code Options (Add suffix to code)



3 Hour Maintained
Emergency
M



Photocell
C



Anti Tamper Screws
T