



1 70 08

VDE FULLY INSULATED DIAGONAL SIDE CUTTERS

Manufactured to DIN ISO 5749 Specifications. Tested to EN 60900
Professional Quality, tested to 10,000V and insulated to 1000V AC and 1500V DC for live line working. Manufactured from vanadium electric steel, oil hardened and tempered. Swedish pattern with smoothly ground heads and separately induction hardened cutting edges to 62HRC. Will cut hard, medium-hard and soft wires. Heavy insulated handles with slip guards for extra comfort and safety. Display packed.

Stock No.	Overall Length	Cutting Capacities-mm		
		Soft Wire dia.	Med Hard Wire dia.	Hard Wire dia.
32020	125mm	3.0	2.3	1.5
31925	140mm	4.0	2.5	1.8
31926	160mm	4.0	3.0	2.0
32021	180mm	4.0	3.0	2.5

High leverage joint = extra cutting power



2 74 08

VDE INSULATED HIGH LEVERAGE DIAGONAL SIDE CUTTERS

Manufactured to DIN ISO 5749 Specifications. Tested to EN 60900
Professional Quality, tested to 10,000V and insulated to 1000V AC and 1500V DC for live line working. Manufactured from chrome vanadium electric steel, oil hardened and tempered. Smoothly ground heads with cutting edges separately induction hardened to 64HRC for cutting piano, hard and soft wires. The cutter has no conventional centre rivet, but a forged-on pivot which can withstand extra leverage. Heavy insulated handles with slip guards for extra comfort and safety. Display packed.

Stock No.	Overall Length	Soft Wire dia.	Cutting Capacities-mm		
			Med Hard Wire dia.	Hard Wire dia.	Piano dia.
32022	160mm	4.0	3.4	2.5	2.0
31927	180mm	4.0	3.8	2.7	2.2
31929	200mm	4.0	4.2	3.0	2.5



Stock No.32023



Stock No.32014

3 95 18

VDE FULLY INSULATED CABLE SHEARS

Tested to EN 60900
Professional Quality, tested to 10,000V and insulated to 1000V AC and 1500V DC for live line working. Forged from special tool steel, hardened and tempered. Smoothly ground head with cutting edges precision ground and hardened. Suitable for cutting, stripping and dismantling. Heavy insulated handles. With slippguards for extra comfort and safety. Display packed.

Stock No.	Overall Length	Cutting Capacity Cu + Al Cables
32014	165mm	15mm dia. - 50mm ²
32023	200mm	20mm dia. - 70mm ²



4 20 08

VDE FULLY INSULATED FLAT NOSE PLIERS

Manufactured to DIN ISO 5745 Specifications. Tested to EN 60900
Professional Quality, tested to 10,000V and insulated to 1000V AC and 1500V DC for live line working. Manufactured from special tool steel, oil hardened and tempered. Smoothly ground polished head, short flat jaws with serrated gripping surfaces. Heavy insulated handles with slip guards for extra comfort and safety. Display packed.

Stock No.	Overall Length	Length	Jaw Dimensions:	
			W-mm Base	Thickness-mm Base
31968	160mm	30.0mm	17.0	9.5



5 22 08

VDE FULLY INSULATED ROUND NOSE PLIERS

Manufactured to DIN ISO 5745 Specifications. Tested to EN 60900
Professional Quality, tested to 10,000V and insulated to 1000V AC and 1500V DC for live line working. Manufactured from special tool steel, oil hardened and tempered. Short round jaws with smooth gripping surfaces ideal for forming wire loops. Heavy insulated handles with slip guards for extra comfort and safety. Display packed.

Stock No.	Overall Length	Length	Jaw Dimensions:	
			W-mm Base	Thickness-mm Tip
31990	160mm	30.0mm	18.0	3.0



6 11 08

VDE FULLY INSULATED WIRE STRIPPING PLIERS

Tested to EN 60900
Professional Quality, tested to 10,000V and insulated to 1000V AC and 1500V DC for live line working. Manufactured from special tool steel, oil hardened and tempered. Smoothly ground accurate V shaped polished jaw head with locking adjustable screw for setting to the desired diameter. Can be used for solid or stranded wire up to 5mm (10mm²) diameter. Internal screw for one hand adjustment. Heavy insulated handles with slip guards for extra comfort and safety. Display packed.

Stock No.	Overall Length
31930	160mm

