

SOCKET BOX TIMERS



- Ideal for most heating applications
- Timer 'on' status indicator
- Fits a 25mm dual appliance socket box should you require the timer next to a fused spur or socket outlet
- Will fit directly to any 25mm deep socket box fitted with an earth terminal
- T108A-C is suitable for discharge lighting applications



T100A-C



T101A-C



T105A-C



T108A-C

	T100A-C	T101A-C	T105A-C	T108A-C
Product Finish	White	White	White	White
Description	24hr Mechanical	7 Day Mechanical	7 Day Electronic with 150hr battery backup	7 Day Electronic
Product Dimensions	H77 x W72 x D43mm Plate 86 x 86mm	H77 x W72 x D43mm Plate 86 x 86mm	H77 x W72 x D43mm Plate 86 x 86mm	H77 x W72 x D43mm Plate 86 x 86mm
Product weight	130g	130g	150g	150g
Barcode	5012739638671	5012739638688	5012739638695	5012739638701
Voltage	230V AC	230V AC	230V AC	230V AC
Display	Mechanical - Analogue clock face	Mechanical - Analogue clock face - minute hand indicator	Electronic - Digital display	Electronic - Digital display
Max Load	16A Resistive load, 2A Inductive load	16A Resistive load, 2A Inductive load	16A Resistive load, 2A Inductive load	16A Resistive load, 8A Inductive load
Settings	96 on/off, On/timed/off switch selector	84 on/off, On/timed/off switch selector	24 on/off, Summer time setting option	Summer time setting option and 'Random' setting
Guarantee	1 Year	1 Year	1 Year	1 Year
Certification & Conformity	IEC 60730-1, IEC 60730-2-7, KEMA-KEUR BS Certification mark BS EN 60730-2-7:2010	IEC 60730-1, IEC 60730-2-7, KEMA-KEUR BS Certification mark BS EN 60730-2-7:2010	IEC 60730-1, IEC 60730-2-7, KEMA-KEUR BS Certification mark BS EN 60730-2-7:2010	IEC 60730-1, IEC 60730-2-7, KEMA-KEUR BS Certification mark BS EN 60730-2-7:2010



Tel +44 (0) 1279 772 772
 Fax +44 (0) 1279 422 007
 www.greenbrook.co.uk

