

CEILING ACCESSORIES



The KingShield dimmable pull switch is able to dim standard and low voltage lighting.



DIMPULLSW-C



GB2641BR-C



GB2641CH-C



GB2641



GB2319

	DIMPULLSW-C	GB2641BR-C	GB2641CH-C	GB2641	GB2319
Product Finish	Chrome/White	Brass	Chrome	White	White
Description	Dimmable Pull Switch Comes complete with both white & chrome covers & acorns	Pull cord switch	Pull cord switch	Pull cord switch	45A DP Switch with neon
Product Dimensions	78mm Dia	83mm Dia	83mm Dia	83mm Dia	86mm x 86mm
Product weight	114g	95g	95g	95g	197g
Barcode	5012739628009	5012739606205	5012739606199	5012739619823	5012739619687
Wattage	Standard Lighting Max Load:250W LV Lighting Max load: 170W Not suitable for LEDs	1380W	1380W	1380W	10350W
Max Operating Current	1.1A	6A, 2 way	6A, 2 way	6A, 2 way	45A, DP
Pack Quantity	1	1	1	10	10
Guarantee	1 Year	1 Year	1 Year	1 Year	1 Year
Main housing material	Urea	Urea	Urea	Urea	Urea
Certification & Conformity	EN 60669-2-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1	BS EN 60669-1

**GREEN
BROOK**
ELECTRICAL

Tel +44 (0) 1279 772 772
Fax +44 (0) 1279 422 007
www.greenbrook.co.uk

