

# 110V Portable Site Transformer



## Description

The Briticent range of portable site transformers covers from 750VA to 5kVa intermittent ratings for stepping down the standard UK mains voltage to a safety 110V centre-tapped earth (CTE) supply.

## Features

- Portable
- Centre tapped earth
- 32A and 16A IP44 socket outlets
- 13A BS1363 plug with 2m lead
- Robust GRP Case

## Range

750VA Premium	750/1
750VA Standard	750/1/B
1000VA Premium	1000/2
1000VA Standard	1000/2/B
1500VA Premium	1500/2
1500VA Standard	1500/2/B
3000VA Premium	3000/2
3000VA Standard	3000/2/B
5000VA Premium	5000/3
5000VA Standard	5000/3/B

## Technical Specification

Input Voltage	230V
Output Voltage	110V
IP Rating	IP44

## Output rating

	Continues	Intermittent
750VA	375VA	750VA
1000VA	500VA	1kVA
1500VA	750VA	1.5kVA
3000VA	1.65kVA	3kVA
5000VA	2.5kVA	5kVA

## Standards

- BS 1363
- BS EN 60309
- BS EN 61558

## Sockets and weights

	32A Sockets	16A Sockets	Weight
750VA	-	1	12kg
1000VA	-	2	12.5kg
1500VA	-	2	13kg
3000VA	-	2	17kg
5000VA	1	2	29kg

Briticent Site Electrics  
2-8 Laporte Way, Luton  
Bedfordshire England  
LU4 8RJ  
Email: sales@briticent.co.uk  
Tel: +44 (0)1582 544590  
Fax: +44 (0)1582 544591