




Pond lights.

01604 495 151
collingwoodlighting.com

 @collingwoodLED

 /collingwoodlighting

 collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

- Complete with wall fixings
- Robust cable for use outdoors
- Tilt & rotate for adjusting light



UL010

Universal LED light

FEATURES

Wattage	3W
IP rating	IP68
Colour flexibility	Fixed colour
Tilttable	360°
Rotatable	360°
Dimmable	N/A
Input	700mA
LED lifetime	70,000h L70 B10
SDCM	3SDCM

INSTALLATION INFORMATION

Bathroom zone	0
Construction material	Stainless steel (316)
Weight	567g
Maximum ambient temperature	35°C
SELV	N/A
Electric class [1, 2, 3]	3

PHOTOMETRICS @ 25°C

Product code	Colour	Beam angle	CRI	lm	lm/W	lx at 1m
UL010 NW	4000K	18°	>80Ra	119	40	648
UL010 WW	3000K	18°	>80Ra	95	32	411
UL010 27	2700K	18°	>80Ra	92	31	399
UL010 BL	Blue	18°	-	-	-	-

WIRING INFORMATION

Cable / flying lead	3m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of wiring required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/700 3-9	220-240V	Yes	No	1	3	9
PLD UNI-DRIVE 700mA	220-240V	Yes	Yes (1-10V)	2	1	10

ACCESSORIES

JB2 / JB4	Waterproof junction box / Gel filled waterproof connector	Sold separately	422-423
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold separately	422
WCR 275 BLACK	2-core rubber cable	Sold separately	423

Beam angle: 18°

