

## WL060

Straight to mains LED halo / flood wall light

#### **FEATURES**

Wattage	2.6W
IP rating	IP65
Colour flexibility	Fixed colour
Tiltable	No
Rotatable	No
Dimmable	No
Input	Mains AC
LED lifetime	70,000h L70 B10
SDCM	3SDCM

#### **INSTALLATION INFORMATION**

Bathroom zone	2
Inrush current	9A 0.8ms
Construction material	Anodised aluminium
Weight	0.6kg
Maximum ambient temperature	40°C
SELV	Yes
Electric class (1, 2, 3)	1

### Wall lights.

# O1604 495 151colspan="2">colspan="2">colspan="2">colspan="2">colspan="2">colspan="2">colspan="2"Image: Colspan="2">Image: Colspan="2">Colspan="2"Image: Colspan="2">Colspan="2"Image: Colspan="2">Colspan="2"Image: Colspan="2">Colspan="2"

#### **GUARANTEE / WARRANTY**

7 year extended warranty

#### **FEATURES & BENEFITS**

Bi-directional wall light offering decorative halo effect and functional downward flood light

Straight to mains

Complete with wall fixings and waterproof crimp connectors

#### PHOTOMETRICS @ 25°C

Product code	Finish	Colour	Beam angle	CRI	lm	lm/W	lx at 1m
WL060 NW	Silver	4000K	110°	>80Ra	82	32	46
WL060 WW	Silver	3000K	110°	>80Ra	58	22	26
WL060 27	Silver	2700K	110°	>80Ra	56	22	25

#### WIRING INFORMATION

Cable / flying lead	0.3m
Type of wiring required	Parallel

#### LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	N/A	N/A	N/A

#### ACCESSORIES

N/A

No accessories required

#### Beam angle: 110°



