




Pond lights.

01604 495 151
collingwoodlighting.com

-  @collingwoodLED
-  /collingwoodlighting
-  collingwoodled



GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

- Improved look and feel with single LED
- Complete with wall fixings
- Tilt & rotate for adjusting light
- Marine grade stainless steel 316
- Long lifetime of 70,000hrs

Beam angle: 12° 40°



UL030

High output universal LED light

FEATURES

Wattage	7W
IP rating	IP68
Colour flexibility	Fixed colour
Tilttable	360°
Rotatable	360°
Dimmable	N/A
Input	Driver required
LED lifetime	70,000h L70 B10
SDCM	3SDCM

INSTALLATION INFORMATION

Bathroom zone	0
Construction material	Stainless steel (316)
Weight	645g
Maximum ambient temperature	50°C
SELV	N/A
Electric class (1, 2, 3)	3

PHOTOMETRICS @ 25°C

Product code	Colour	Beam angle	CRI	lm	lm/W	lx at 1m
UL030DWBX40	4000K	40°	>80Ra	490	109	1050
UL030DNBX40	4000K	12°	>80Ra	490	109	7975
UL030DWBX30	3000K	40°	>80Ra	480	107	1029
UL030DNBX30	3000K	12°	>80Ra	480	107	7812
UL030DWBX27	2700K	40°	>80Ra	470	104	1007
UL030DNBX27	2700K	12°	>80Ra	470	104	7649

WIRING INFORMATION

Cable / flying lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of wiring required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/700 3-9	220-240V	Yes	No	1	1	1
PLD UNI-DRIVE 700mA	220-240V	Yes	Yes (1-10V)	2	1	6

ACCESSORIES

JB2 / JB4	Waterproof junction box / Gel filled waterproof connector	Sold separately	422-423
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold separately	422
WCR 275 BLACK	2-core rubber cable	Sold separately	423