



DM298GRID


LED mains grid dimmer

FEATURES

Product code	DM298GRID
Construction material	Plastic
Dimmer type	Push on / off, rotary dial dim
Grid plate adaptors	White adaptors for Hamilton, MK, BG, Crabtree, Schneider, DETA, Hager & Wandsworth grid ranges
Mains supply voltage	240V AC
Mains supply voltage range	230V AC - 240V AC
Mains supply frequency	50Hz
Load type	LED dimmable driver only
Minimum load capacity	5W
Maximum load capacity	100W / 10 LED units max.
Phase firing	Trailing edge dimming
Connection terminals	3mm ² max.
Back box depth	35mm min.
Surface temperature	40°C

USE WITH

H2 Lite
H2 Lite 500
H2 Lite 500 CSW
H2 Lite 500 CSP
H2 Pro 550
H2 Pro 550 SPS
H2 Pro 550 CS
H2 Pro 700
H2 Pro Elect
H2 Pro Elect Trimless
H4 Lite
H4 Pro 550
H4 Pro 550 SPS
H4 Pro 700
H4 Pro Elect
H5 Trimless
DL120 / DL130
FIBRE LED LIGHT
RL111
DM02



DM298FP

Faceplate dimmer

FEATURES

Product Code	DM298FP
Construction material	Plastic
Dimmer type	Push on / off, rotary dial dim
Grid plate adaptors	-
Mains supply voltage	240V AC
Mains supply voltage range	230V AC - 240V AC
Mains supply frequency	50Hz
Load type	LED dimmable driver only
Minimum load capacity	5W
Maximum load capacity	100W / 10 LED units max.
Phase firing	Trailing edge dimming
Connection terminals	3mm ² max.
Back box depth	35mm min.
Surface temperature	40°C

USE WITH

H2 Lite
H2 Lite 500
H2 Lite 500 CSW
H2 Lite 500 CSP
H2 Pro 550
H2 Pro 550 SPS
H2 Pro 550 CS
H2 Pro 700
H2 Pro Elect
H2 Pro Elect Trimless
H4 Lite
H4 Pro 550
H4 Pro 550 SPS
H4 Pro 700
H4 Pro Elect
H5 Trimless
DL120 / DL130
FIBRE LED LIGHT
RL111
DM02

