




Spike lights.

01604 495 151
collingwoodlighting.com

 @collingwoodLED

 /collingwoodlighting

 collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

Equivalent to 35W halogen

Long spike included for extra stability

Robust cable for outdoor use

Hooded for reduced glare



SL040A

High output LED spike light

FEATURES

Wattage	7W
IP rating	IP65
Colour flexibility	Fixed colour
Tilttable	90°
Input	Driver required (700mA)
LED lifetime	70,000h L70 B10
SDCM	3SDCM

INSTALLATION INFORMATION

Bathroom zone	1
Inrush Current	N/A
Construction material	Anodised aluminium
Weight	600g
Maximum ambient temperature	35°C
SELV	Yes
Electric class (1, 2, 3)	3

PHOTOMETRICS @ 25°C

Product code	Finish	Colour	Beam angle	CRI	lm	lm/W	lx at 1m
SL040A F NW	Black	4000K	38°	>80Ra	520	74	1471
SL040A S NW	Black	4000K	18°	>80Ra	520	74	4614
SL040A F WW	Black	3000K	38°	>80Ra	413	59	1168
SL040A S WW	Black	3000K	18°	>80Ra	413	59	3665
SL040A F 27	Black	2700K	38°	>80Ra	377	54	1066
SL040A S 27	Black	2700K	18°	>80Ra	377	54	3345

WIRING INFORMATION

Cable / flying lead	3m H05RN-F rubberised cable (outside diameter: 6mm)
Type of wiring required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/700 3-9	220V-240V	Yes	No	1	1	3
PL/IP/700 1-3	220V-240V	Yes	No	1	1	1
PLD UNI-DRIVE 700MA	220V-240V	Yes	Yes (1-10V)	2	1	3

ACCESSORIES

JB2 / JB4 / JB6	Waterproof junction box / Gel filled waterproof connectors	422-423
WCR 275 BLACK	2-core rubber cable	423
PDC/GRID DIMMER	1-10V dimmer module	422

Beam angle: 18° 38°

