




Ground lights.

01604 495 151
collingwoodlighting.com

 @collingwoodLED

 /collingwoodlighting

 collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

- Compact yet powerful fitting
- Shallow depth for easy installation
- Robust cable for outdoor use
- Built-in glare reducing honeycomb baffle



GL019 LG

1W mini low glare LED ground light

FEATURES

Wattage	1W
IP rating	IP68
IK rating	IK07
Colour flexibility	Fixed colour
UGR	<10
Walk over / drive over	Walk over (5mm toughened glass)
Input	350mA / 700mA
LED lifetime	70,000h L70 B10
SDCM	3SDCM

INSTALLATION INFORMATION

Cut out size	Ø 33mm
Bathroom zone	0
Inrush current	N/A
Construction material	Stainless steel (316)
Weight	204g
Maximum ambient temperature	50°C
SELV	N/A
Electric class [1, 2, 3]	3

PHOTOMETRICS @ 25°C

Product code	Colour	Beam angle	CRI	lm	lm/W	Lx at 1m
GL019LGFNW	4000K	30°	>80Ra	65	65	262
GL019LGSNW	4000K	12°	>80Ra	65	65	908
GL019LGFWW	3000K	30°	>80Ra	55	55	222
GL019LGSWW	3000K	12°	>80Ra	55	55	768
GL019LGF27	2700K	30°	>80Ra	53	53	214
GL019LGS27	2700K	12°	>80Ra	53	53	740

WIRING INFORMATION

Cable / flying lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of wiring required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	9
PLR/350 1-5	N/A	Yes	No	0	1	5
PLD UNI-DRIVE 350MA	N/A	Yes	Yes (1-10V)	1	1	10

ACCESSORIES

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold separately	422-423
TUBE332	Installation tube	Sold separately	236
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold separately	422

