

GU10 Downlight

Fire-rated fixed IP20 downlight

FEATURES

IP rating	IP20
Tiltable	No
Input	Mains AC



Install connector type	Push-fit terminal connector
Insulation coverable	No
Cut out size	Ø 79mm
Construction material	Mild steel
Maximum ceiling thickness	40mm
Weight	0.213g
Building regulations	Part B, C, E, P
Electric class (1, 2, 3)	1

PRODUCT CODE

Product code	Finish	Description	
CWFRC001	Matt white	GU10 Fire rated downlight, Fixed, IP20, White	
CWFRC002	Brushed steel	GU10 Fire rated downlight, Fixed, IP20, Brushed steel	
CWFRC003	Polished chrome	GU10 Fire rated downlight, Fixed, IP20, Polished chrome	

WIRING INFORMATION

Cable / flying lead	N/A
Cable required for connector	Push-fit terminal for: Twin & Earth (6242Y 2x1.5mm²)
Type of wiring required	Parallel

Residential downlights.

01604 495 151 collingwoodlighting.com CollingwoodLED () /collingwoodlighting

O collingwoodled

GUARANTEE / WARRANTY

3 year extended warranty

FEATURES & BENEFITS

Loop-in loop-out connector for ease of installation

30, 60, 90 min fire rating providing additional safety

Acoustic and moisture tested

6-Watt LED or 50-Watt halogen lamp compatible for additional versatility IP20

Lamp not included

