



Frosted LED drive over ground / marker light

FEATURES

Wattage	8W
IP rating	IP67
IK rating	IK10
Colour flexibility	Fixed colour
Walk over / drive over	Drive over (15mph maximum)
Input	Mains AC
LED lifetime	70,000h L70 B10
SDCM	3SDCM

INSTALLATION INFORMATION

Bathroom zone	2
Inrush current	10.7A 0.7ms
Construction material	Stainless steel 304 (cover ring) / Aluminium (body)
Weight	2.7Kg
Maximum ambient temperature	35°C
SELV	Yes
Electric class (1, 2, 3)	1

PHOTOMETRICS @ 25°C

Product code	Colour	Beam angle	CRI	lm	lm/W	lx at 1m
GL007 FROSTED NW	4000K	120°	>80Ra	101	13	43
GL007 FROSTED WW	3000K	120°	>80Ra	96	12	33

WIRING INFORMATION

Cable / flying lead Type of wiring required 1m H05RN-F rubberised cable (outside diameter: 7mm) Parallel

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
N/A (integrated SELV driver)	220-240V	-	No	2	-	-

ACCESSORIES

Installation tube		Included	101
JB5	Gel filled waterproof connector	Sold separately	423
WC 5-9	Quick waterproof connector	Sold separately	422

Ground lights.

01604 495 151 collingwoodlighting.com

CollingwoodLED

f /collingwoodlighting

O collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

Frosted effect for softer tone of light

Straight to mains

Installation tube included

10mm toughened glass, ideal for use in driveways



