



# T5 Triphosphor




At only 16mm diameter, the T5 linear fluorescent range is used in slim luminaires and fixtures and is available in High Efficiency (HE) for maximum energy saving or High Output (HO) for maximum lumen output.

- 20,000 hour life
- 85/1B colour rendering index/group
- SPECTRA-PLUS Triphosphor
- 3500K white, 4000K cool white or 6500K daylight colour options
- Excellent colour rendering and high lumen maintenance
- Designed for use with High Frequency ballasts



Product Code	Watts (W)	Cap	Colour Appearance	Colour Temp (K)	Total Lumens (lm)	Colour Rendering Index/Group	Dimensions (mm)			Energy Rating	Order Qty
							Dia	L1	L2		
<b>High Efficiency (HE) - Single Sleeve</b>											
FTT514SPW	14	G5	White	3500	1205	85/1B	16	549	562	A	30
FTT514SPCW	14	G5	Cool White	4000	1205	85/1B	16	549	562	A	30
FTT514SPDYLT	14	G5	Daylight	6500	1100	85/1B	16	549	562	A	30
FTT521SPW	21	G5	White	3500	1900	85/1B	16	849	862	A+	30
FTT521SPCW	21	G5	Cool White	4000	1900	85/1B	16	849	862	A+	30
FTT528SPW	28	G5	White	3500	2605	85/1B	16	1149	1162	A+	30
FTT528SPCW	28	G5	Cool White	4000	2605	85/1B	16	1149	1162	A+	30
FTT528SPDYLT	28	G5	Daylight	6500	2400	85/1B	16	1149	1162	A	30
FTT535SPW	35	G5	White	3500	3300	85/1B	16	1449	1462	A+	30
FTT535SPCW	35	G5	Cool White	4000	3300	85/1B	16	1449	1462	A+	30
FTT535SPDYLT	35	G5	Daylight	6500	3050	85/1B	16	1449	1462	A	30
<b>High Output (HO) - Single Sleeve</b>											
FTT524SPCW	24	G5	Cool White	4000	1755	85/1B	16	549	562	A	30
FTT524SPDYLT	24	G5	Daylight	6500	1600	85/1B	16	549	562	A	30
FTT539SPCW	39	G5	Cool White	4000	3100	85/1B	16	849	862	A	30
FTT554SPCW	54	G5	Cool White	4000	4450	85/1B	16	1149	1162	A	30
FTT549SPCW	49	G5	Cool White	4000	4315	85/1B	16	1449	1462	A	30
FTT549SPDYLT	49	G5	Daylight	6500	3950	85/1B	16	1449	1462	A	30
FTT580SPCW	80	G5	Cool White	4000	6160	85/1B	16	1449	1462	A	30

See page 88 for LED alternative



G5 Cap

