



LED T5 Direct to Mains Full Glass Tube



LED T5 full glass tube with external diffused sleeve providing 270° light output. Energy saving with low power consumption. Direct to mains for maximum efficiency no ballast required*. Instant full light.

- 40,000 hour life
- 15,000 switching cycles
- 4000K cool white
- Available in 2ft, 3ft, 4ft or 5ft T5 lengths
- Colour rendering index Ra≥80
- Ambient operating temperature -20°C to 50°C
- No mercury no warping, no bending
- No discolouration of light over life of tube
- Not suitable for dimming
- Not suitable for emergency circuits
- Recommended for indoor use only
- Supplied in a rigid 2mm cardboard tube to minimise transportation damage



| Product Code | Watts (W) | Volts (V) | Cap | Colour Appearance | Colour Temp (K) | Total Lumens (lm) | Beam Angle | Dimensions (mm) | | | Energy Rating | Order Qty |
|----------------------|-----------|-----------|-----|-------------------|-----------------|-------------------|------------|-----------------|------|------|---------------|-----------|
| | | | | | | | | Dia | L1 | L2 | | |
| Single Carton | | | | | | | | | | | | |
| 12080 | 8 | 240 | G5 | Cool White | 4000 | 780 | 270° | 16 | 563 | 549 | A+ | 1 |
| 12097 | 12 | 240 | G5 | Cool White | 4000 | 1100 | 270° | 16 | 863 | 849 | A+ | 1 |
| 12066 | 16 | 240 | G5 | Cool White | 4000 | 1580 | 270° | 16 | 1163 | 1149 | A+ | 1 |
| 12073 | 20 | 240 | G5 | Cool White | 4000 | 2400 | 270° | 16 | 1463 | 1449 | A+ | 1 |

* Direct to mains only. Do not run with a ballast, re-wiring by a qualified person may be required, see website for instructions.

