



### Colour Finish

- Black - HR\_/B
- White - HR\_/W
- Titanium - HR\_/X



### LED Types

- LED 600 (HR2 only).
- LED 1800 (HR3 only).

### Materials

- Body: 283mm / 353mm vandal resistant polycarbonate with self-extinguishing fire properties.
- Diffuser / Fascia Ring: Vandal resistant polycarbonate in opal with self extinguishing fire properties.
- Diffuser 2: (353mm circular) Vandal resistant polycarbonate clear lens with self-extinguishing fire properties.
- Die-cast aluminium option available (HR3 only).

### Installation


- Wall or ceiling mount.
- BESA fixing and rear cable entry. 3 way mains terminal block. 4 way terminal block for emergency versions & photocell.
- Screw down lid.
- Photocell version - external use only.
- HI-LO PIR - 100% light output, dims to 10% during periods of inactivity.
- 2 x Conduit entry points (mini version only).

### Standards

- IP65.
- 20 Joules of impact resistance (IK10).
- BS EN 60598.
- Class I.



| Size     | HR2   | HR3   |
|----------|-------|-------|
| Diameter | 283mm | 353mm |
| Depth    | 103mm | 110mm |



### Colour Finish

- Black - HR\_/B
- White - HR\_/W
- Titanium - HR\_/X



### LED Types

- LED 600 (HR2 only).
- LED 1800 (HR3 only).

### Materials

- Body: 283mm / 353mm vandal resistant polycarbonate with self-extinguishing fire properties.
- Diffuser / Fascia Ring: Vandal resistant polycarbonate in opal with self extinguishing fire properties.
- Diffuser 2: (353mm circular) Vandal resistant polycarbonate clear lens with self-extinguishing fire properties.
- Die-cast aluminium option available (HR3 only).

### Installation


- Wall or ceiling mount.
- BESA fixing and rear cable entry. 3 way mains terminal block. 4 way terminal block for emergency versions & photocell.
- Screw down lid.
- Photocell version - external use only.
- HI-LO PIR - 100% light output, dims to 10% during periods of inactivity.
- 2 x Conduit entry points (mini version only).

### Standards

- IP65.
- 20 Joules of impact resistance (IK10).
- BS EN 60598.
- Class I.




| Size     | HR2   | HR3   |
|----------|-------|-------|
| Diameter | 283mm | 353mm |
| Depth    | 113mm | 122mm |



| Code            | Size  | Colour | Diffuser     | Colour Temp. | System Power | Delivered Lumens | Efficacy  |
|-----------------|-------|--------|--------------|--------------|--------------|------------------|-----------|
| HR2/BLP4LED600  | 283mm | Black  | Premium Opal | 4000 K       | 7.4 W        | 466.7 lm         | 63.2 lm/W |
| HR3/BLP4LED1800 | 353mm | Black  | Premium Opal | 4000 K       | 15.8 W       | 1535 lm          | 97.3 lm/W |

Code options (add suffix to code)



Excludes - HR2/BLP4LED600



Photocell C



PIR P




HI-LO PIR HILO



Excludes - HR2/BLP4LED600




Metal Base Option HR3M/



eMotion™ Cloud Wireless Mesh -EMCC

| Code            | Size  | Colour | Diffuser     | Colour Temp. | System Power | Delivered Lumens | Efficacy  |
|-----------------|-------|--------|--------------|--------------|--------------|------------------|-----------|
| HR2/BLL4LED600  | 283mm | Black  | Premium Opal | 4000 K       | 7.4 W        | 267.1 lm         | 36.2 lm/W |
| HR3/BLL4LED1800 | 353mm | Black  | Premium Opal | 4000 K       | 15.7W        | 857.4lm          | 54.6lm/W  |

Code options (add suffix to code)



Excludes - HR2/BLL4LED600



Photocell C




PIR P




HI-LO PIR HILO



Excludes - HR2/BLL4LED600



Metal Base Option HR3M/



eMotion™ Cloud Wireless Mesh -EMCC