

**PHOEBE
LED**

ATLAS-MINI LED SLIMLINE FLOODLIGHT

NEW



20

Energy efficient integrated LED slim-line floodlights with or without PIR sensor.

- Long life 35,000 hours maintenance free operation, 15,000 switching cycles
- Fully IP65 rated, including the PIR sensor - suitable for use outdoors
- -20°C to 40°C operating temperature
- Die-cast aluminium with black powder coat finish, stylish thin body design
- Angled mounting bracket for ease of installation without the need to disassemble the fitting
- Includes 80cm VDE cable

PIR Sensor Models

- Controls for sensitivity, time and lux levels
- 120° monitoring angle
- Override option for PIR models*
- Max detection range selectable up to 8m
- Light hold after detection selectable from 10 seconds to 7 minutes

Product Code	Watts (W)	Volts (V)	Colour Appearance	Colour Temp (K)	Useful Lumens (lm)	Total Lumens (lm)	Beam Angle	Halogen Equiv. (W)	Dimensions (mm)			Order Qty	
									W	H	D		
Single Carton										W	H	D	
12554	10	240	Cool White	4000	660	750	110°	60	127	102	26	1	
12561	20	240	Cool White	4000	1350	1500	110°	100	159	121	28	1	
12578	30	240	Cool White	4000	2090	2200	110°	150	197	145	29	1	
12585	50	240	Cool White	4000	3290	4000	110°	200	243	178	32	1	
With PIR - Single Carton													
12592	10	240	Cool White	4000	660	750	110°	60	127	149	55	1	
12608	20	240	Cool White	4000	1350	1500	110°	100	159	169	55	1	
12615	30	240	Cool White	4000	2090	2200	110°	150	197	191	55	1	
12622	50	240	Cool White	4000	3290	4000	110°	200	243	224	55	1	

*Includes override function - turn on/off/on to override PIR

