

# Calinor LED Polycarbonate Floodlight

Supplied c/w Integral Driver

- Compact and economic polycarbonate LED floodlight
- Warm and Cool white options
- 30W LED comparable light output of 35W HQI  
50W LED exceeds performance of 70W HQI
- Polished faceted reflector and textured glass for optimum performance
- Pre-wired with 1 metre of rubber insulated cable for ease of installation
- PIR versions complete with manual override facility
- LED lifespan L70 30,000 hours
- Non-dimmable



PIR



5 - 12 Metres  
10 Seconds - 8 Minutes  
3 Lux - PC Off



ACALED30




ACALED30/PIR




ACALED50




ACALED50/PIR




ACALED30



ACALED30/PIR



ACALED50



ACALED50/PIR

## LED Information

Cool White      Warm White

Total (Watts)	30W	
	50W	
Lumens Delivered		
30W	2708lm	2701lm
50W	4770lm	4511lm
Lm/W 30W	97lm	97lm
Lm/W 50W	99lm	94lm
CRI	Ra 70	
CCT	4000K	
	3000K	
Input	230V	
Hertz	50Hz	
Operating Temp	-10°C to 40°C	

	Code	Lamp	Description
Standard	ACALED30	LED	30W - Cool White
PIR	ACALED30/PIR	LED	30W c/w PIR - Cool White
Standard	ACALED50	LED	50W - Cool White
PIR	ACALED50/PIR	LED	50W c/w PIR - Cool White
Standard	ACALED30/WW	LED	30W - Warm White
PIR	ACALED30/WW/PIR	LED	30W c/w PIR - Warm White
Standard	ACALED50/WW	LED	50W - Warm White
PIR	ACALED50/WW/PIR	LED	50W c/w PIR - Warm White

