

# Infinite LED Recessed Panel

Supplied c/w Remote Driver

388



Powered by  
**TRIDONIC**  
▼ enlightening your ideas



Surface Mounting Frame for LED Panel  
(shown with Panel Pod installed)

Code	Lamp	Description
<b>AIRMLED/CW</b>	LED	36W - Cool White
<b>AIRMLED/WW</b>	LED	36W - Warm White
<b>Emergency</b> AIRMLED/POD/3NM/ST	LED	5W - Cool White Panel Pod Emergency
<b>Sensor</b> AIRMLED/POD/MWS		1W - Microwave Sensor
<b>Option</b> /DD		Digital Dimming
<b>Accessories</b> AIRMLED/SMF		Surface Mounting Frame (L600mm x W600mm x D75mm)
AIRMLED/PRK		Plasterboard Recessing Kit (Cut-out 608x608mm)
AIRMLED/SK		2 Metre Suspension Kit

- High performance LED flat panel which outperforms Moduni 3x14W T5
- UGR<19 (unified glare rating) compliant luminaire ideal for most interior lighting applications
- Maintenance free instant light output and unlimited switching
- LED lifespan L70 40,000 hours
- Dimmable options

\* 7 Year Warranty applies to fittings registered online (5 Year Warranty for unregistered fittings)

Dimensions (mm)  
L595 x W595 x H10

See p394 for more information on Panel Pod Emergency and Panel Pod Sensor

## LED Information

Total (Watts)	36W
Lumens Delivered	
Cool White	3300lm
Warm White	3100lm
Lm/W Cool White	81lm
Lm/W Warm White	75lm
CRI Cool White	Ra 80
CCT Cool White	4750K
CCT Warm White	3500K
Input	230V
Hertz	50Hz
Operating Temp	-10°C to 40°C



\* Subject to ceiling/installation types  
\* Not applicable to surface/suspended applications