

# Calinor LED Polycarbonate Floodlight

Supplied c/w Integral Driver



ACALED10



ACALED10/PIR



ACALED20







ACALED20/PIR



5 - 12 Metres  
10 Seconds - 8 Minutes  
3 Lux - PC Off

- Compact and economic polycarbonate LED floodlight
- Warm and Cool white options
- 10W LED ideal for halogen replacement  
20W LED exceeds performance of 20W HQI
- Polished faceted reflector and textured glass for optimum performance
- Pre-wired with 1 metre of rubber insulated cable for ease of installation (500mm for 10W)
- PIR versions complete with manual override facility
- LED lifespan L70 30,000 hours
- Non-dimmable



## LED Information

	Cool White	Warm White
<b>Total (Watts)</b>		10W 20W
<b>Lumens Delivered</b>		
10W	942lm	892lm
20W	1924lm	1807lm
Lm/W 10W	94lm	89lm
Lm/W 20W	96lm	90lm
CRI	Ra 70	
CCT	4000K 3000K	
Input	230V	
Hertz	50Hz	
Operating Temp	-10°C to 40°C	

	Code	Lamp	Description
Standard	ACALED10	LED	10W - Cool White
PIR	ACALED10/PIR	LED	10W c/w PIR - Cool White
Standard	ACALED20	LED	20W - Cool White
PIR	ACALED20/PIR	LED	20W c/w PIR - Cool White
Standard	ACALED10/WW	LED	10W - Warm White
PIR	ACALED10/WW/PIR	LED	10W c/w PIR - Warm White
Standard	ACALED20/WW	LED	20W - Warm White
PIR	ACALED20/WW/PIR	LED	20W c/w PIR - Warm White

