



- LED linklight with integral driver for domestic applications
- Exceeds performance of T5 fluorescent equivalent
- Up to 50% energy savings compared to fluorescent equivalents
- Moulded spine fitted with integral switch and fixed diffuser
- Linkable up to a maximum of twelve fittings
- LED lifespan L70 50,000 hours
- Non-dimmable



### LED Information

	Cool White	Warm White
<b>Total (Watts)</b>	3W	
	7W	
	13W	
	18W	
<b>Lumens Delivered</b>	273lm	247lm
	710lm	646lm
	1366lm	1305lm
	1752lm	1749lm
<b>Lm/W</b>	91lm	82lm
	101lm	92lm
	98lm	93lm
	97lm	97lm
<b>CRI</b>	Ra 60	
<b>CCT</b>	4000K	
	3000K	
<b>Input</b>	230V	
<b>Hertz</b>	50/60Hz	
<b>Operating Temp</b>	-5°C to 40°C	

	Code	Lamp	Description	Length	Width	Depth
<b>Cool White</b>	<b>AMALED20/CW</b>	LED	3W - Cool White	220	22.8	38.4
	<b>AMALED50/CW</b>	LED	7W - Cool White	525	22.8	38.4
	<b>AMALED80/CW</b>	LED	13W - Cool White	858	22.8	38.4
	<b>AMALED120/CW</b>	LED	18W - Cool White	1158	22.8	38.4
<b>Warm White</b>	<b>AMALED20/WW</b>	LED	3W - Warm White	220	22.8	38.4
	<b>AMALED50/WW</b>	LED	7W - Warm White	525	22.8	38.4
	<b>AMALED80/WW</b>	LED	13W - Warm White	858	22.8	38.4
	<b>AMALED120/WW</b>	LED	18W - Warm White	1158	22.8	38.4
<b>Accessories</b>	<b>A250TLL/T5</b>		250mm Link Lead			
	<b>A500TLL/T5</b>		500mm Link Lead			
	<b>A1000TLL/T5</b>		1000mm Link Lead			



# Aspen LED Linklight

Supplied c/w Integral Driver



- High performance LED Linklight with integral driver
- Suitable for commercial and domestic applications
- Output exceeds T5 fluorescent equivalent
- Metal spine fitted with integral switch and fixed diffuser
- Linkable up to a maximum of twelve fittings
- LED lifespan L70 63,000 hours
- Non-dimmable



## LED Information

Cool White      Warm White

Total (Watts)	6W	
	10W	
	16W	
	22W	
Lumens Delivered	535lm	531lm
	928lm	871lm
	1660lm	1373lm
	2205lm	2090lm
Lm/W	89lm	89lm
	103lm	87lm
	111lm	92lm
	100lm	95lm
CRI	Ra 80	
CCT	4000K	
	3000K	
Input	230V	
Hertz	50/60Hz	
Operating Temp	-5°C to 40°C	

	Code	Lamp	Description	Length	Width	Depth
<b>Cool White</b>	<b>ALEDKL/30</b>	LED	6W - Cool White	321	29	39
	<b>ALEDKL/60</b>	LED	10W - Cool White	550	29	39
	<b>ALEDKL/90</b>	LED	16W - Cool White	883	29	39
	<b>ALEDKL/120</b>	LED	22W - Cool White	1183	29	39
<b>Warm White</b>	<b>ALEDKL/30/WW</b>	LED	6W - Warm White	321	29	39
	<b>ALEDKL/60/WW</b>	LED	10W - Warm White	550	29	39
	<b>ALEDKL/90/WW</b>	LED	16W - Warm White	883	29	39
	<b>ALEDKL/120/WW</b>	LED	22W - Warm White	1183	29	39
<b>Accessories</b>	<b>A250TLL/T5</b>	250mm Link Lead				
	<b>A500TLL/T5</b>	500mm Link Lead				
	<b>A1000TLL/T5</b>	1000mm Link Lead				



# T5 Triphosphor Linklight

Supplied c/w Lamp

170



- Fitted with integral switch and diffuser
- Linkable up to 6 fittings using optional 250mm, 500mm and 1000mm leads
- Fixing brackets supplied to allow either vertical or horizontal installation
- Lamp colour 3400k




Code	Lamp	Description	Length	Width	Depth
<b>A6TP/T5</b>	T5	6W	278	22	43
<b>A8TP/T5</b>	T5	8W	358	22	43
<b>A14TP/T5</b>	T5	14W	618	22	43
<b>A21TP/T5</b>	T5	21W	916	22	43
<b>A28TP/T5</b>	T5	28W	1215	22	43
<b>A35TP/T5</b>	T5	35W	1515	22	43

## Accessories

<b>Link Leads</b>	<b>A250TLL/T5</b>	250mm
	<b>A500TLL/T5</b>	500mm
	<b>A1000TLL/T5</b>	1000mm

**A**      **B**

Tubes	Code	Description	A	B
	<b>A6TT/T5</b>	6W	225	212
	<b>A8TT/T5</b>	8W	302	288
	<b>A14TT/T5</b>	14W	564	548
	<b>A21TT/T5</b>	21W	862	848
	<b>A28TT/T5</b>	28W	1162	1147
	<b>A35TT/T5</b>	35W	1462	1448



CE □ HF IP20