


# Kite LED Emergency Bulkhead

Supplied with Legend and Integral Driver

408



- Modern ultra-slim profile
- IP65 LED polycarbonate bulkhead
- Self-test as standard
- Aesthetically designed for modern appearance
- Supplied with self-adhesive legend
- 20mm side and rear cable entries
- Hinged screwless gear tray for ease of installation
- Viewing distance 20 metres



***	Escape route 2 metres wide (1 Lux minimum) *				
	Mounting Height (M)	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial
	2.5	3.4	6	3.2	7.2
	4	3.5	8.8	3	8
	6	-	-	-	-

***	Open (Anti-Panic) area (0.5 Lux Minimum) **				
	Mounting Height (M)	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial
	2.5	3.5	6.5	2.6	7
	4	3.6	8	3.2	8.6

\* 1 lux minimum must be used for all marked emergency escape routes, to be measured down the centre line of the escape route itself

\*\* 0.5 lux minimum must be used for areas larger than 60m<sup>2</sup>, the maximum value is to be measured across the area excluding 0.5 metre border around the edge of the room

\*\*\* Explanation of the symbols:-  
**Transverse - Wall**  
 Distance to wall from side of fitting  
**Transverse - Transverse**  
 Side to side spacing  
**Axial - Wall**  
 Distance to wall from end of fitting  
**Axial - Axial**  
 End to end spacing

## LED Information

Total (W)	3W
Lumens Delivered	
Emergency Mode	68lm
Standard Mode	123lm
CCT	6500K
Input	230V
Hertz	50/60Hz
Operating Temp	0C° to 45C°

	Code	Lamp	Description
Self-Test	AKTLED/3M/ST	LED	3W Maintained / Non-Maintained
Accessory	ASBP/1		3.6V 600mAh Ni-Cd Replacement Battery

