
## Harrier LED IP65 Blade Exit Sign

Supplied c/w Self-Adhesive Legend (Optional Blade Legend ordered separately)



- Compact high performance IP65 polycarbonate surface emergency luminaire
- Self-test as standard
  Optional hanging blade legends (supplied with self-adhesive legend as standard) for enhanced appearance
- Aesthetically designed for modern appearance
- High output LED performance and distribution allows maximum spacing providing reduced cost
- Viewing distance
  25 metres



- \* 1 lux minimum must be used for all marked emergency escape routes, to be measured down the centre line of the escape route itself
- \*\* 0.5 lux minimum must be used for areas larger than 60m<sup>2</sup>, the maximum value is to be measured across the area excluding 0.5 metre border around the edge of the room
- \*\*\* Explanation of the symbols:-Transverse - Wall Distance to wall from side of fitting Transverse - Transverse Side to side spacing Axial - Wall Distance to wall from end of fitting Axial - Axial End to end spacing

	Code	Lamp	Description
Self-Test	AHARLED/3M/ST	LED	6W Maintained/Non-Maintained
Legends	AHARLED/ALAR	Harrier LED Double Sided Legend - Arrow Left and Right	
	AHARLED/L/AD	Harrier LED Double Sided Legend - Arrow Down	
	AHARLED/L/AU	Harrier L	ED Double Sided Legend - Arrow Up
Battery	ASBP/5	7.2V 1500	mAh Ni-Cd Replacement Battery



Total (W)	6W
Lumens Delivered	
Emergency Mode	120lm
Standard Mode	299lm
CCT	6500K
Input	230V
Hertz	50/60Hz
Operating Temp	0C° to 45C°

(E 🖶 IP65





