



Centurion LED Bulkhead

Supplied c/w Legend and Integral Driver



- High lumen performance LED polycarbonate bulkhead for increased spacings
- Supplied with self-adhesive legend
- Self-test as standard
- Outperforms 8W T5 and exceeds performance of Guardian by 56%
- 20mm conduit entry positions and rear terminal box entry
- Hinged screwless gear tray for ease of installation
- Viewing distance 18 metres
- 50,000 hours average lifetime



* 1 lux minimum must be used for all marked emergency escape routes, to be measured down the centre line of the escape route itself

** 0.5 lux minimum must be used for areas larger than 60m², the maximum value is to be measured across the area excluding 0.5 metre border around the edge of the room

*** Explanation of the symbols:-
Transverse - Wall
 Distance to wall from side of fitting
Transverse - Transverse
 Side to side spacing
Axial - Wall
 Distance to wall from end of fitting
Axial - Axial
 End to end spacing



***	Escape route 2 metres wide (1 Lux minimum) *				
Mounting Height (M)	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial	
2.5	3.65	7.4	3.4	7.2	
4	3.65	7.75	3.5	7.5	
6	-	-	-	-	

***	Open (Anti-Panic) area (0.5 Lux Minimum) **				
Mounting Height (M)	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial	
2.5	3.5	7.2	3.4	6.8	
4	4.6	8.8	3.3	6.9	
6	5	10.2	3.6	7.3	

LED Information

Total (W)	6W
Lumens Delivered	
Emergency Mode	150lm
Standard Mode	229lm
CCT	6500K
Input	230V
Hertz	50/60Hz
Operating Temp	0C° to 45C°

	Code	Lamp	Description
Self-Test	ACELED/3M/ST	LED	6W Maintained / Non-Maintained
Accessory	ASBP/2		3.6V 1500mAh Ni-Cd Replacement Battery

