

## Fire Rated LED Downlights

### Tiltable Fire Rated Downlights - Lux Fire Tiltable

This premium LED downlight offers the efficiency of LED, the safety of fire rating certification and the flexibility of an adjusting, tiltable design.

The recessed COB LED provides a low-glare, high-quality light that can be tilted to illuminate specific areas or features in a room. The lamp is IP65 and fire rated to 30, 60 and 90 minutes and is air-tight and sound resistant. The stylish body means the downlight looks great either on or off.

- Complete with dimmable or non-dimmable Loop-in / Loop-out driver
- IP65 and Air Tightness Compliant with Part C and Part L
- Resistance to Sound Compliant with Part E



**Applications:** Commercial and domestic; including reception areas, boardrooms, hospitality, retail, living rooms, kitchens and hallways.



Deep recessed LED  
for discreet lighting  
and low-glare



Choose from a high  
quality satin nickel  
or white bezel



Moisture and dust proof silicone  
seal prevents air and heat loss

### PART B Fire safety

Product tested to BS 476 Part 21 to confirm compliance for fire resistance of load bearing floors are not compromised by fitting the downlight. Tested for 30, 60 and 90 minutes fire resistance constructions.





1



2

Product Code	Cut-out mm	Watts (W)	Eq Watts (W)	Temp K	Lumens lm	Lumens per watt	CRI >=	Beam Angle	Finish	L1 Compliant	L2 Compliant	Pic.
<b>Fire Rated Downlight</b> - with clear diffuser and dimmable driver, supplied with white or satin nickel bezel									35,000 hrs, 3 year warranty			
<b>Dimmable</b>												
ILD LFR92C001	92	6	41	3000	430	72	80	36°	White	✓	✓	1
ILD LFR92C003	92	6	41	4000	450	75	80	36°	White	✓	✓	1
ILD LFR92C005	92	9	51	3000	650	72	80	36°	White	✓	✓	1
ILD LFR92C006	92	9	55	4000	680	76	80	36°	White	✓	✓	1
ILD LFR92C007	92	9	51	3000	650	72	80	55°	White	✓	✓	1
ILD LFR92C008	92	9	55	4000	680	76	80	55°	White	✓	✓	1
ILD LFR92C009	92	11	62	3000	850	77	80	55°	White	✓	✓	1
ILD LFR92C010	92	11	64	4000	890	81	80	55°	White	✓	✓	1
ILD LFR92C015	92	6	40	3000	430	72	80	36°	Satin Nickel	✓	✓	2
ILD LFR92C016	92	6	41	4000	450	75	80	36°	Satin Nickel	✓	✓	2
ILD LFR92C017	92	11	62	3000	850	77	80	55°	Satin Nickel	✓	✓	2
ILD LFR92C018	92	11	64	4000	890	81	80	55°	Satin Nickel	✓	✓	2
<b>Non-Dimmable</b>												
ILD LFR92C002	92	6	41	3000	420	70	80	36°	White	✓	✓	1
ILD LFR92C004	92	6	41	4000	430	72	80	36°	White	✓	✓	1

## Choice of 5 interchangeable scalloped metal bezels



White

ILD LFR92C019




Polished Chrome

ILD LFR92C011



Satin Nickel

ILD LFR92C013



Antique Brass

ILD LFR92C020



Copper

ILD LFR92C021

Product Code	Description
<b>Accessories for Lux Fire Downlight</b>	
I LEMPK010*	2.5W 3hr Emergency Kit
I LEMAK012	Male and female connector for Lux Fire - Fire Rated Downlights and emergency kit I LEMPK010

\*In emergency mode light output will be 10% of the total lumens