Lightspan

NEW

NEW

Integral Lightspan Battens provide an efficient alternative to T8 fluorescent tube fittings. At up to 7800lm, Lightspan battens are ideal for indoor commercial spaces that need bright task lighting and at up to 120lm/W they offer big energy savings compared to equivalent fluorescent fittings.



Product Code	IP Rating	Watts (W)	Temp K	Lumens Im	Lumens per watt	Beam Angle	Description	Dimensions mm*	Pic.		
Lightspan T8 Style LED Batten											
Non-Dimmable	!										
ILBTC051	IP20	43	4000	5150	119	140°	LED Batten 43W 4ft	1170 x 60 x 71 mm	1		
ILBTC053	IP20	60	4000	7200	120	140°	LED Batten 60W 5ft	1470 x 60 x 71 mm	1		
ILBTC055	IP20	65	4000	7800	120	140°	LED Batten 65W 6ft	1734 x 60 x 71 mm	1		
PIR Sensor with Remote Control for Battens with 20mm connector opening											
ILBTASE057	PIR Batten Sensor 85-265V AC 50/60HZ IP65 PIR 0-10V Dimming Remote Control										

Value+ IP20 LED Battens

Integral Value+ IP20 LED Battens are perfect for work benches, shelving areas and stock rooms. At 100lm/W these LED battens are an ideal replacement for traditional fluorescent tube lights, providing energy savings over their lifetime.

The Value+ range has a white injection moulded housing and a diffuser for even light distribution. This range comes pre-wired and fixing brackets are also included for easy installation. The rear of the batten provides flexibility to hide the cable resulting in a discreet finish.







Product Code	IP Rating	Watts (W)	Temp K	Lumens Im	Lumens per watt	Beam Angle	Description	Dimensions mm*	Pic.
Value+ IP20 LE	30,000 hrs, 3 year warranty								
Non-Dimmable									
ILBTC036	IP20	9	4000	900	100	130°	LED Batten 9W 2ft	600 x 27 x 36 mm	3
ILBTC037	IP20	18	4000	1800	100	130°	LED Batten 18W 4ft	1200 x 27 x 36 mm	3
ILBTC038	IP20	22	4000	2200	100	130°	LED Batten 22W 5ft	1500 x 27 x 36 mm	3
ILBTC039	IP20	9	6500	900	100	130°	LED Batten 9W 2ft	600 x 27 x 36 mm	3
ILBTC040	IP20	18	6500	1800	100	130°	LED Batten 18W 4ft	1200 x 27 x 36 mm	3
ILBTC041	IP20	22	6500	2200	100	130°	LED Batten 22W 5ft	1500 x 27 x 36 mm	3