

Candle



Product Code	Base	Watts (W)	Eq Watts (W)	Temp K	Lumens lm	Lumens per watt	CRI >=	Beam Angle	Diffuser	Energy Rating	Pic.
Candle										15,000 hrs, 2 year warranty	
Non-Dimmable											
ILCANDB22NC008	B22	3.1	25	2700	250	80	80	260°	Frosted	A+	1
ILCANDB22NC011	B22	3.1	25	2700	250	80	80	230°	Clear	A+	2
ILCANDB22NC003	B22	3.6	25	2700	250	69	80	300°	Frosted	A+	1
ILCANDB22NF023	B22	5.4	40	5000	500	89	80	240°	Clear	A+	3
ILCANDB22NC016	B22	5.5	40	2700	470	85	80	280°	Frosted	A+	1
ILCANDB22NF017	B22	5.5	40	5000	500	100	80	280°	Frosted	A+	1
ILCANDB22NC022	B22	5.5	40	2700	470	85	80	240°	Clear	A+	3
ILCANDE27NC018	E27	5.5	40	2700	470	85	80	240°	Clear	A+	4
ILCANDE27NC012	E27	5.5	40	2700	470	85	80	280°	Frosted	A+	5
ILCANDE14NC032	E14	3.4	25	2400	200	59	80	280°	Frosted	A+	6
ILCANDE14NC006	E14	3.4	25	2700	250	73	80	280°	Frosted	A+	6
ILCANDE14NC009	E14	3.4	25	2700	250	80	80	240°	Clear	A+	3
ILCANDE14NC005	E14	5	40	2700	470	94	80	300°	Frosted	A+	6
ILCANDE14NC019	E14	5.5	40	2700	470	85	80	240°	Clear	A+	3
ILCANDE14NF021	E14	5.5	40	5000	520	94	80	240°	Clear	A+	3
ILCANDE14NF015	E14	5.5	40	5000	500	91	80	280°	Frosted	A+	7
ILCANDE14NC013	E14	5.5	40	2700	470	85	80	280°	Frosted	A+	8
ILCANDE14NC054	E14	7.5	60	2700	806	107	80	280°	Frosted	A+	6
ILCANDE14NF055	E14	7.5	61	5000	830	111	80	280°	Frosted	A+	6
ILCANDB15NC010	B15	3.4	25	2700	250	80	80	240°	Clear	A+	3
ILCANDB15NC007	B15	3.4	25	2700	250	73	80	280°	Frosted	A+	6
ILCANDB15NC020	B15	5.5	40	2700	470	85	80	240°	Clear	A+	3
ILCANDB15NC014	B15	5.5	40	2700	470	85	80	280°	Frosted	A+	6
Dimmable - with compatible dimmers											
ILCANDB22DC030	B22	5.6	40	2700	470	75	80	240°	Clear	A+	9
ILCANDB22DC025	B22	6.2	40	2700	470	75	80	240°	Frosted	A+	1
ILCANDB22DF031	B22	6.2	40	5000	480	77	80	240°	Clear	A+	9
ILCANDB22DF027	B22	5.6	40	5000	500	89	80	280°	Frosted	A+	1
ILCANDE14DC028	E14	5.6	40	2700	470	83	80	240°	Clear	A+	3
ILCANDE14DC024	E14	5.6	40	2700	470	83	80	240°	Frosted	A+	8
ILCANDE14DF029	E14	5.6	40	5000	480	77	80	240°	Clear	A+	10
ILCANDE14DF026	E14	5.6	40	5000	500	89	80	280°	Frosted	A+	8