

GLS



Product Code	Base	Watts (W)	Eq Watts (W)	Temp K	Lumens lm	Lumens per watt	CRI >=	Beam Angle	Diffuser	Energy Rating	Pic.
GLS											15,000 hrs, 2 year warranty
Non-Dimmable											
ILGLSB22NC005	B22	5.5	40	2700	470	85	80	300°	Frosted	A+	1
ILGLSB22NC010	B22	6	40	2700	470	78	80	260°	Frosted	A+	2
NEW ILGLSB22NF071	B22	6	43	5000	500	111	80	260°	Frosted	A+	3
ILGLSB22NC012	B22	9.5	60	2700	806	84	80	200°	Frosted	A+	4
NEW ILGLSB22NF073	B22	9.5	60	5000	806	111	80	200°	Frosted	A+	4
ILGLSB22NC014	B22	11	75	2700	1060	96	80	200°	Frosted	A+	5
ILGLSB22NF016	B22	11	75	5000	1060	96	80	200°	Frosted	A+	5
ILGLSB22NC018	B22	13	100	2700	1521	112	80	150°	Frosted	A+	6
ILGLSB22NF031	B22	13.5	100	5000	1521	112	80	200°	Frosted	A+	5
ILGLSB22NC049	B22	18	120	2700	1921	107	80	230°	Frosted	A+	7
ILGLSB22NF051	B22	18	120	5000	2000	111	80	230°	Frosted	A+	7
ILGLSE27NC029	E27	5.6	40	2400	350	63	80	240°	Frosted	A+	2
ILGLSE27NC006	E27	5.8	40	2700	470	81	80	300°	Frosted	A+	1
ILGLSE27NC009	E27	6	40	2700	470	78	80	240°	Frosted	A+	5
NEW ILGLSE27NF070	E27	6	43	5000	500	111	80	260°	Frosted	A+	3
ILGLSE27NC011	E27	9.5	60	2700	806	84	80	240°	Frosted	A+	3
NEW ILGLSE27NF072	E27	9.5	60	5000	806	111	80	200°	Frosted	A+	3
ILGLSE27NC013	E27	11	75	2700	1060	96	80	200°	Frosted	A+	8
ILGLSE27NF015	E27	11	75	5000	1060	96	80	200°	Frosted	A+	9
ILGLSE27NC017	E27	13.5	100	2700	1521	117	80	200°	Frosted	A+	10
ILGLSE27NF030	E27	13.5	100	5000	1521	112	80	200°	Frosted	A+	11
ILGLSE27NC048	E27	18	120	2700	1921	107	80	230°	Frosted	A+	7
ILGLSE27NF050	E27	18	120	5000	2000	111	80	230°	Frosted	A+	7
Dimmable - with compatible dimmers											
ILGLSB22DC020	B22	5.5	40	2700	470	85	80	240°	Frosted	A+	12
ILGLSB22DC022	B22	8.5	60	2700	806	95	80	240°	Frosted	A+	12
NEW ILGLSB22DC083	B22	10	60	2700	806	85	80	240°	Frosted	A+	9
ILGLSB22DC024	B22	12	75	2700	1060	88	80	240°	Frosted	A+	13
ILGLSB22DC033	B22	15	100	2700	1521	101	80	240°	Frosted	A+	11
ILGLSE27DC019	E27	5.5	40	2700	470	85	80	240°	Frosted	A+	2
ILGLSE27DC021	E27	8.5	60	2700	806	94	80	240°	Frosted	A+	9
NEW ILGLSE27DC084	E27	10	60	2700	806	85	80	260°	Frosted	A+	9
ILGLSE27DC023	E27	10.5	75	2700	1100	104	80	240°	Frosted	A+	13
ILGLSE27DC032	E27	13.5	100	2700	1521	112	80	150°	Frosted	A+	8