

Description

Firebreak Qr10 COB Downlight, supplied complete with remote plug & play dimmable driver.



General

Colour Options	White, Chrome, Brushed Chrome
Light Source	CREE LED COB, Non Replaceable Module
LED Expected Life	40,000 Hours
Product Warranty	3 Years from Date of Purchase
Mounting Method	Ceiling Recessed Only

Electrical Parameters

Supply Voltage	220-240V AC
Frequency	50Hz
Circuit Wattage	10W Including Diver
Circuit Current	0.04 Amps
Driver mA Rating	200mA
PFC	0.9
In Rush Current	0.4Amps

Classifications and Approvals

Earth Class	Class II, With Earth Provision
IP Rating	IP65
Fire Rating (Part B)	Yes
Sound Insulating (Part E)	Yes
Air & Moisture Rated (Part C)	Yes
Efficiency Rated (Part L)	Yes
Energy Rating	A+
CE Marked	Yes
Designed In Accordance to	BSEN60598, EN55015

Installation

Cut-out	72mm
Minimum Void	90mm
Insulation	Driver Must Remain in Free Air Space
Working Ambient Temp.	0°C to +40°C
Primary Connections	Loop In/Out Push In Terminals On Driver
Secondary Connections	Plug & Play Head Unit to Driver
Accessories	Optional Colour Rims Available

Performance

Luminous Flux	675 Lumens
Luminous Efficacy (L/pw)	67 L/pw
CCT	4000k
CRI (Ra)	Ra80
Beam Angle	46°
Dimmable	Yes, See Website for List of Approved Dimmers
Tilt/Rotate	No Fixed Position

Construction

Main Chassis	Mild Steel
Trim/Bezel	Cast Aluminium
Diffuser	N/A
Lens	Polycarbonate
Heat Sink	Aluminium
Finish Type	Powder Coat Paint/Plated Finish

