

GLS BULB B22 1521LM 13W 2700K NON-DIMM 200 BEAM FROSTED INTEGRAL

ILGLSB22NC018



This 13W retro-fit Integral LED Classic Globe (GLS) (large bayonet base) delivers a warm light and brightness. With a 1521 lumen output, this lamp is one of only a few true 100W filament bulb replacements available today. It features high output LEDs, an anti-glare refractor, all finished in an aluminium and plastic, thermally efficient body. Ideal for rooms with a single pendant fitting, living rooms, hallways and kitchens.

Details

Quick Order Code: 343420

Barcode: 5055788208068

Category:LampsRange Name:EverydayProduct Type:GLSWarranty (Years):2CE RoHS:Yes

Physical Data

Product Length (mm): 121
Product Width (mm): 60
Product Weight (g): 185

Material: Plastic, Polycarbonate, Nickel plated brass

Base Term: Bayonet cap

Bulb Base: B22

Construction: Aluminium heat-sink, Injection moulded diffuser

Globe Finish: Frosted
Globe Type: GLS
Bulb or Luminaire Shape: Round

Placement / Application: Indoor, General Lighting

Electrical Data

Power (W): 13, 13.5
Power Consumption (w): 13.5, 13
Power Factor: 0.5
Wattage equivalent (W): 100
Amperage (mA): 118

Dimming: Non-Dimmable

Driver IC Manufacturer:

Driver Included:

Electric Current:

Silergy

Yes

AC

EN: EN-62560

LVD Certified: Yes

Light Data

Luminous Flux in Lumens (lm): 1521 Luminous efficacy (lm/W): 117 Correlated Colour Temperature (CCT) (K): 2700

Colour Temperature: 2700K - Warm

Colour Temperature Name:WarmBeam Angle:150, 200Colour Rendering Index (CRI):80Instant on (Less than 1 second):Yes


LED Type: Surface mounted device (SMD)

Lifetime (hours): 15000 Switching Cycles: 7500

Environment

EN: EN-62560

LVD Certified: Yes **CE RoHS:** Yes **Energy Rating:** A++ **New Energy Rating:** Ε Hg 0% (Mercury Free): Yes **IP Rating (Ingress Protection):** IP20 **Lowest Operating Temperature (°C):** -20 **Maximum Operating Temperature (°C):** 40



Packaging

Package Weight (g): Portal.int@33al-led.com

Package Length (mm): 135

Package Width (mm): 68
Package Depth (mm): 68
Qty per euro pallet: 1050