

**OMNI FILAMENT GLS BULB E27 806LM 7.3W 2700K DIMMABLE 320 BEAM  
CLEAR FULL GLASS INTEGRAL**

ILGLSE27DC054

Integral Filament Omni GLS Lamps utilise Filament LED technology and a full-glass body to create a decorative look and wide beam angle that looks fantastic in ceiling pendants and fittings where the lamp is exposed. These retrofit lamps are highly efficient and are an ideal replacement for traditional tungsten filament bulbs.

**Details**

<b>Quick Order Code:</b>	265298
<b>Barcode:</b>	5055788222453
<b>Category:</b>	Lamps
<b>Range Name:</b>	Omni
<b>Product Type:</b>	GLS
<b>Market Segment:</b>	Commercial indoor
<b>Warranty (Years):</b>	2
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Length (mm):</b>	104
<b>Product Width (mm):</b>	60
<b>Product Weight (g):</b>	32
<b>Material:</b>	Glass
<b>Base Term:</b>	Edison screw
<b>Bulb Base:</b>	E27
<b>Construction:</b>	Glass shell, filament strip
<b>Globe Finish:</b>	Clear
<b>Globe Type:</b>	GLS
<b>Bulb Fixing:</b>	Pendant, Wall, lamp stand, table lamp
<b>Bulb or Luminaire Shape:</b>	Round
<b>Placement / Application:</b>	Indoor, General Lighting

**Electrical Data**

<b>Power (W):</b>	7.3
<b>Power Consumption (w):</b>	7.3
<b>Power Factor:</b>	0.5


<b>Wattage equivalent (W):</b>	60
<b>Amperage (mA):</b>	45
<b>Dimming:</b>	Dimmable
<b>Driver Included:</b>	Yes
<b>Electric Current:</b>	AC
<b>EN:</b>	EN-62560
<b>LVD Certified:</b>	Yes

## Light Data

<b>Luminous Flux in Lumens (lm):</b>	806
<b>Luminous efficacy (lm/W):</b>	110
<b>Correlated Colour Temperature (CCT) (K):</b>	2700
<b>Colour Temperature:</b>	2700K - Warm
<b>Colour Temperature Name:</b>	Warm
<b>Beam Angle:</b>	320
<b>Colour Rendering Index (CRI):</b>	80
<b>Instant on (Less than 1 second):</b>	Yes
<b>LED Type:</b>	Filament chip
<b>Lifetime (hours):</b>	15000

## Environment

<b>EN:</b>	EN-62560
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>Energy Rating:</b>	A+
<b>New Energy Rating:</b>	E
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IP Rating (Ingress Protection):</b>	IP20
<b>Lowest Operating Temperature (°C):</b>	-20
<b>Maximum Operating Temperature (°C):</b>	45



## Packaging

<b>Package Weight (g):</b>	55	<a href="http://Portal.integral-led.com">Portal.integral-led.com</a>
<b>Package Length (mm):</b>	65	

Product Design And Specification Subject To Change Or Modification Without Notice. Image For Illustration Only. E&OE

<b>Package Width (mm):</b>	65
<b>Package Depth (mm):</b>	120
<b>Qty per euro pallet:</b>	1350