

GLS BULB B22 1055LM 10.5W 2700K DIMMABLE 220 BEAM FROSTED INTEGRAL

ILGLSB22DC024



This 10.5W retro-fit Integral LED Classic Globe (GLS) (large bayonet base) delivers a dimmable, warm light and brightness, similar to a 75W filament bulb. It features high output LEDs, an anti-glare refractor, all finished in an aluminium and plastic, thermally efficient body. Ideal for living rooms, hallways and kitchens.

Details

Quick Order Code: 854158

Barcode: 5055788209911

Category:LampsRange Name:EverydayProduct Type:GLSWarranty (Years):2CE RoHS:Yes

Physical Data

Product Length (mm): 103
Product Width (mm): 60
Product Weight (g): 150

Material: Plastic, Polycarbonate, Nickel plated brass

Base Term: Bayonet cap

Bulb Base: B22

Construction: Aluminium and Plastic heat-sink, Injection moulded

diffuser

Globe Finish: Frosted
Globe Type: GLS
Bulb or Luminaire Shape: Round

Placement / Application: Indoor, General Lighting

Electrical Data

Power (W):	10.5
Power Consumption (w):	10.5
Power Factor:	0.7
Wattage equivalent (W):	75
Amperage (mA):	55

Dimming: Dimmable

Driver IC Manufacturer: Power Integrations (PI)

Driver Included: Yes
Electric Current: AC

EN: EN-62560

LVD Certified: Yes

Light Data

Luminous Flux in Lumens (Im): 1055 Luminous efficacy (Im/W): 101 Correlated Colour Temperature (CCT) (K): 2700

Colour Temperature: 2700K - Warm

Colour Temperature Name:WarmBeam Angle:220Colour Rendering Index (CRI):80Instant on (Less than 1 second):Yes


LED Type: Surface mounted device (SMD)

Lifetime (hours): 15000 Switching Cycles: 12500

Environment

EN: EN-62560

LVD Certified: Yes **CE RoHS:** Yes **Energy Rating:** A+ **New Energy Rating:** F Hg 0% (Mercury Free): Yes **IP Rating (Ingress Protection):** IP20 **Lowest Operating Temperature (°C):** -20 **Maximum Operating Temperature (°C):** 40



Packaging

Package Weight (g): Portal.int@gral-led.com

Package Length (mm): 65

Package Width (mm): 65
Package Depth (mm): 120