

# VALUE+ PANEL 600X600 3800LM 38W 4000K DRIVER NOT INCLUDED 100LM/W EDGELIT INTEGRAL

ILP6060E008



This is a 38W, 3800lm 600x600 Integral LED Value+ panel. It delivers a uniform cool white light across the whole of its surface. The high level of efficacy (100lm/W) offers savings in running cost against traditional 72W fluorescent fittings as well as many other LED panels. The panels are an ideal solution for many applications. No driver is supplied with this panel.

### **Details**

Quick Order Code: 150077

**Barcode**: 5055788229711

Category:PanelsRange Name:Value+Product Type:600 x 600Product Body Finish:Matt white

Market Segment: Commercial indoor

Warranty (Years): 3
CE RoHS: Yes

## **Physical Data**

Product Length (mm): 596
Product Depth (mm): 8.2
Product Width (mm): 596
Product Weight (g): 2000

Optic: Opal diffuser

Material: Aluminium, Steel, PS Diffuser

**Construction:** extruded Aluminium, steel back, LGP sheet and PS

diffuser

**Luminaire Fixing:** Recessed in ceiling grid, surface mounted or

suspended (additional surface mounted or suspension

kit required)

Placement / Application: Indoor, General Lighting

#### **Electrical Data**

Power (W): 38
Power Consumption (w): 38

Wattage equivalent (W): 86.4 Amperage (mA): 835

**Dimming:** Dimmable

Driver Included: No Electric Current: AC

**EN:** EN-60598

LVD Certified: Yes

# **Light Data**

Luminous Flux in Lumens (Im): 3800
Luminous efficacy (Im/W): 100
Peak Intensity (Cd): 1004
Correlated Colour Temperature (CCT) (K): 4000

Colour Temperature: 4000K - Cool White

Colour Temperature Name: Cool White

Beam Angle:110Colour Rendering Index (CRI):80Instant on (Less than 1 second):YesLED Size (mm):2835

**LED Type:** Surface mounted device (SMD)

Lifetime (hours):30000Lighting Method:Edge-litSwitching Cycles:25000

#### **Environment**

**EN:** EN-60598

LVD Certified: Yes **CE RoHS:** Yes Hg 0% (Mercury Free): Yes IP20 IP Rating (Back/Recessed side): **IP Rating (Ingress Protection):** IP20 **Lowest Operating Temperature (°C):** -10 **Maximum Operating Temperature (°C):** 40 TP rating: None

# **Packaging**

Package Weight (g): 3300
Package Length (mm): 686
Package Width (mm): 640
Package Depth (mm): 40
Qty per euro pallet: 75