

VALUE+ CEILING/WALL LIGHT 300MM DIA IP44 1200LM 16W 4000K 120 BEAM NON-DIMM 75LM/W INTEGRAL

ILBHE026



Low-energy LED IP44 Value+ ceiling and wall light, suitable for all indoor areas such as hallways, stairways, walls and ceilings including bathrooms (Zone 2) and covered (sheltered) external areas, such as porches. PMMA Diffuser provides a soft light. Long life expectancy of 25,000 hours based on normal usage. 2 year warranty.

Details

Quick Order Code:	399596
Barcode:	5055788223672
Category:	Luminaires
Range Name:	Value+
Product Type:	Bulkheads-Ceiling-Wall Lights
Product Body Finish:	Matt white
Market Segment:	Commercial indoor, Residential indoor
Features:	Standard
Warranty (Years):	2
CE RoHS:	Yes

Physical Data

Product Depth (mm):	85
Product Weight (g):	522
Optic:	PMMA diffuser
Material:	PMMA, Metal
Overall diameter (mm):	300
Construction:	Metal base and PMMA diffuser
Bulb or Luminaire Shape:	Round
Luminaire Fixing:	Ceiling, Wall
Placement / Application:	Indoor, General Lighting
Wiring / Mounting Options:	Rear Only

Electrical Data

Power (W):	16
Power Consumption (w):	16
Power Factor:	0.5

Amperage (mA):	127
Dimming:	Non-Dimmable
Driver Included:	Yes
Electric Current:	AC
Emergency Lumens (lm):	No
EN:	EN-60598
LVD Certified:	Yes

Light Data

Luminous Flux in Lumens (lm):	1200
Luminous efficacy (lm/W):	75
Correlated Colour Temperature (CCT) (K):	4000
Colour Temperature Name:	Cool White
Beam Angle:	120
Colour Rendering Index (CRI):	80
Instant on (Less than 1 second):	Yes
LED Type:	Surface mounted device (SMD)
Lifetime (hours):	25000
Sensor / Override:	No
Switching Cycles:	12500

Environment

EN:	EN-60598
LVD Certified:	Yes
CE RoHS:	Yes
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP44
Lowest Operating Temperature (°C):	0
Maximum Operating Temperature (°C):	40

Packaging

Package Weight (g):	799
Package Length (mm):	325
Package Width (mm):	325
Package Depth (mm):	105
Qty per euro pallet:	60