

# CLASSIC FILAMENT GLS E27 830LM 7W 5000K NON-DIMM 300 BEAM FROSTED INTEGRAL

ILGLSE27NF099



The Classic Full Glass Frosted lamp utilises Filament LED technology to create a decorative look and wide beam angle that looks fantastic in fittings where the lamp is exposed. These retrofit lamps are highly efficient and are an ideal replacement for traditional tungsten filament bulbs.

#### **Details**

Quick Order Code: 882514

**Barcode**: 5055788252443

Category:LampsRange Name:Classic

Market Segment: Commercial indoor, Residential indoor

Warranty (Years): 2
CE RoHS: Yes

### **Physical Data**

Product Length (mm): 108
Product Width (mm): 60
Product Weight (g): 44

Material:Aluminium, GlassBase Term:Edison screw

Bulb Base: E27

**Construction:** Glass shell, Filament strip, Aluminium base

Globe Finish: Frosted

Globe Type: Classic Globe (GLS)

Bulb or Luminaire Shape: Round

Placement / Application: Indoor, General Lighting

#### **Electrical Data**

Power Consumption (w): 7
Power Factor: 0.5
Wattage equivalent (W): 60
Amperage (mA): 60

**Dimming:** Non-Dimmable

Driver Included: Yes

Electric Current: AC
True Wattage Eq (W): 60

**EN:** EN-62560

LVD Certified: Yes

## **Light Data**

Luminous Flux in Lumens (Im): 830 Luminous efficacy (Im/W): 119 Correlated Colour Temperature (CCT) (K): 5000

**Colour Temperature:** 5000K - Daylight

Colour Temperature Name:DaylightBeam Angle:300Colour Rendering Index (CRI):80Instant on (Less than 1 second):Yes


**LED Type:** Filament chip

Lifetime (hours): 15000
Switching Cycles: 7500
Useful Lumens (lm): 400

#### **Environment**

**EN:** EN-62560

LVD Certified: Yes **CE RoHS:** Yes A+ **Energy Rating: New Energy Rating:** E Hg 0% (Mercury Free): Yes IP20 **IP Rating (Ingress Protection): Lowest Operating Temperature (°C):** -20 **Maximum Operating Temperature (°C):** 45



## **Packaging**

Package Weight (g): 64

Package Length (mm): Portal.int@gral-led.com

Package Width (mm): 65

Product Design And Specification Subject To Change Or Modification Without Notice. Image For Illustration Only. E&OE

Package Depth	(mm)·	120
Package Depth	(111111).	120