

OMNI FILAMENT GLS BULB B22 1521LM 11.2W 2700K DIMMABLE 300 BEAM CLEAR INTEGRAL

ILGLSB22DC123



Integral Filament Omni GLS Lamps utilise Filament LED technology to create a decorative look and wide beam angle that looks fantastic in ceiling pendants and fittings where the lamp is exposed. These retrofit lamps are highly efficient and are an ideal replacement for traditional tungsten filament bulbs.

Details

Quick Order Code:	589394
Barcode:	5055788260226
Category:	Lamps
Range Name:	Omni
Market Segment:	Commercial indoor, Residential indoor
Warranty (Years):	2
CE RoHS:	Yes

Physical Data

Product Length (mm):	103
Product Width (mm):	60
Product Weight (g):	54
Material:	Aluminium, Glass
Base Term:	Bayonet cap
Bulb Base:	B22
Construction:	Glass shell, Filament strip, Aluminium base
Globe Finish:	Clear
Globe Type:	GLS
Bulb or Luminaire Shape:	Round
Placement / Application:	Indoor, General Lighting
Spot Type:	Filament

Electrical Data

Power Consumption (w):	11.2
Power Factor:	0.7
Wattage equivalent (W):	100
Amperage (mA):	47
Dimming:	Dimmable with compatible dimmers


Driver Included:	Yes
Electric Current:	AC
True Wattage Eq (W):	100
EN:	EN-62560
LVD Certified:	Yes

Light Data

Luminous Flux in Lumens (lm):	1521
Luminous efficacy (lm/W):	135
Correlated Colour Temperature (CCT) (K):	2700
Colour Temperature:	2700K - Warm
Colour Temperature Name:	Warm
Beam Angle:	320
Colour Rendering Index (CRI):	80
Colour Type:	Single
Instant on (Less than 1 second):	Yes
LED Type:	Filament chip
Lifetime (hours):	15000
Switching Cycles:	7500

Environment

EN:	EN-62560
LVD Certified:	Yes
CE RoHS:	Yes
Energy Rating:	A++
New Energy Rating:	D
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	40



Packaging

Package Weight (g):	110	Portal.integral-led.com
Package Length (mm):	135	

Product Design And Specification Subject To Change Or Modification Without Notice. Image For Illustration Only. E&OE

Package Width (mm): 70
Package Depth (mm): 70