

**LIGHTSPAN T8 BATTEN 4FT TWIN 5600LM 43W 130LM/W 4000K 120 BEAM  
1170mm LINKABLE NON-DIMM INTEGRAL**

ILBTC051



Integral Lightspan Battens provide an efficient alternative to T8 fluorescent tube fittings. With their high lumen output, Lightspan battens are ideal for indoor commercial spaces that need bright task lighting and at up to 130lm/W they offer big energy savings compared to equivalent fluorescent fittings.

**Details**

<b>Quick Order Code:</b>	697540
<b>Barcode:</b>	5055788237006
<b>Category:</b>	Luminaires
<b>Range Name:</b>	Lightspan
<b>Type:</b>	Twin
<b>Product Type:</b>	Battens
<b>Product Body Finish:</b>	Matt white
<b>Market Segment:</b>	Indoor commercial, Industrial, residential
<b>Finish:</b>	Matt White
<b>Warranty (Years):</b>	3
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Length (mm):</b>	1170
<b>Product Depth (mm):</b>	70
<b>Product Width (mm):</b>	60
<b>Product Weight (g):</b>	1250
<b>Optic:</b>	Polycarbonate diffuser
<b>Material:</b>	Polycarbonate, Aluminium
<b>Construction:</b>	Injection moulding
<b>Bulb or Luminaire Shape:</b>	Linear
<b>Luminaire Fixing:</b>	Wall / Ceiling / Pendant / Conduit mounted
<b>Mounting Type:</b>	Rear & Side Cable Entry
<b>Placement / Application:</b>	Indoor, General Lighting

**Electrical Data**

<b>Power Consumption (w):</b>	43
<b>Power Factor:</b>	0.9


<b>Input Voltage (V):</b>	220-240
<b>Dimming:</b>	Non-Dimmable
<b>Driver Included:</b>	Yes
<b>Electric Current:</b>	AC
<b>EN:</b>	EN-60598
<b>LVD Certified:</b>	Yes

## Light Data

<b>Luminous Flux in Lumens (lm):</b>	5600
<b>Luminous efficacy (lm/W):</b>	130
<b>Correlated Colour Temperature (CCT) (K):</b>	4000
<b>Colour Temperature Name:</b>	Cool White
<b>Beam Angle:</b>	120
<b>Colour Rendering Index (CRI):</b>	80
<b>Instant on (Less than 1 second):</b>	Yes
<b>LED Size (mm):</b>	2835
<b>LED Type:</b>	Surface mounted device (SMD)
<b>Lifetime (hours):</b>	30000
<b>Useful Lumens (lm):</b>	5150

## Environment

<b>EN:</b>	EN-60598
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>EU Luminaire:</b>	L
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IK Rating (Impact Protection):</b>	IK08
<b>IP Rating (Ingress Protection):</b>	IP20
<b>Lowest Operating Temperature (°C):</b>	-20
<b>Maximum Operating Temperature (°C):</b>	50



## Packaging

<b>Package Weight (g):</b>	1450	<a href="http://Portal.integral-led.com">Portal.integral-led.com</a>
<b>Package Length (mm):</b>	1175	

Product Design And Specification Subject To Change Or Modification Without Notice. Image For Illustration Only. E&OE

<b>Package Width (mm):</b>	68
<b>Package Depth (mm):</b>	79