

## GLASS GU10 BULB 400LM 3.6W 4000K DIMMABLE 36 BEAM INTEGRAL

ILGU10DE087



The glass body and cleverly engineered surface mounted LEDs of the Integral LED Glass GU10 range give them an attractive look that is very similar to traditional halogen lamps. These GU10 lamps will retrofit easily into existing fittings and provide significant energy savings and longer lifetime than the halogen lamps they are designed to replace.

## **Details**

Quick Order Code: 293576

**Barcode:** 5055788230038

Category:LampsRange Name:GlassProduct Type:GU10

Market Segment: Commercial indoor, Residential indoor

Warranty (Years): 2
CE RoHS: Yes

### **Physical Data**

Product Length (mm): 54
Product Width (mm): 50
Product Weight (g): 50

Optic: Designed to give a Halogen look

Material:GlassBase Term:GU10Bulb Base:GU10

**Construction:** Glass body and "fly eye" diffuser lens

Globe Finish: Dichroic look
Bulb Fixing: Downlight
Bulb or Luminaire Shape: Round

Placement / Application: Indoor, General Lighting
Spot Type: SMD with "COB like effect"

#### **Electrical Data**

Power (W): 3.6
Power Consumption (w): 3.6
Power Factor: 0.4

Wattage equivalent (W): 56
Amperage (mA): 21

Dimming:DimmableDriver IC Manufacturer:SM7307Driver Included:YesElectric Current:ACTrue Wattage Eq (W):50

**EN:** EN-62560

LVD Certified: Yes

# **Light Data**

Luminous Flux in Lumens (Im): 450
Luminous efficacy (Im/W): 111
Peak Intensity (Cd): 800
Correlated Colour Temperature (CCT) (K): 4000

Colour Temperature: 4000K - Cool White

Colour Temperature Name: Cool White

Beam Angle: 36
Colour Rendering Index (CRI): 80

Compatible Dimmers: Varilight JQP401W

Instant on (Less than 1 second): Yes

**LED Type:** Surface mounted device (SMD)

Lifetime (hours): 25000
Switching Cycles: 12500
Useful Lumens (lm): 345

#### **Environment**

**EN:** EN-62560

LVD Certified: Yes **CE RoHS:** Yes **Energy Rating:** A+ **New Energy Rating:** Е Hg 0% (Mercury Free): Yes **IP Rating (Ingress Protection):** IP20 **Lowest Operating Temperature (°C):** -20 **Maximum Operating Temperature (°C):** 40



# **Packaging**

Package Weight (g): 53
Package Length (mm): 55
Package Width (mm): 55
Package Depth (mm): 60
Qty per euro pallet: 2800