

CANDLE BULB B22 470LM 5.6W 2700K DIMMABLE 280 BEAM FROSTED INTEGRAL

ILCANDB22DC025



This 5.6W retro-fit Integral LED Candle (frosted finish, large bayonet, white base) delivers a dimmable, warm light and brightness, similar to a 40W filament bulb. It features high output LEDs and an anti-glare refractor. Ideal for living rooms, dining rooms, bedrooms and hotels, in classic or modern wall or floor/table lamp fittings and chandeliers.

Details

Quick Order Code:	976179
Barcode:	5055788202363
Category:	Lamps
Range Name:	Everyday
Product Type:	Candle
Market Segment:	Commercial indoor, Residential indoor
Warranty (Years):	2
CE RoHS:	Yes

Physical Data

Product Length (mm):	108
Product Width (mm):	38
Product Weight (g):	75
Material:	Plastic, Aluminium, Glass, Nickel plated brass
Base Term:	Bayonet cap
Bulb Base:	B22
Construction:	Plastic and Aluminium heat-sink, glass diffuser
Globe Finish:	Frosted
Globe Type:	Candle
Bulb Fixing:	Pendant, Chandelier, Wall
Bulb or Luminaire Shape:	Oval
Placement / Application:	Indoor, General Lighting

Electrical Data

Power Consumption (w):	5.6
Power Factor:	0.5
Wattage equivalent (W):	40

Amperage (mA):	58
Dimming:	Dimmable
Driver IC Manufacturer:	IWATT
Driver Included:	Yes
Electric Current:	AC
EN:	EN-62560
LVD Certified:	Yes

Light Data

Luminous Flux in Lumens (lm):	470
Luminous efficacy (lm/W):	84
Correlated Colour Temperature (CCT) (K):	2700
Colour Temperature Name:	Warm
Beam Angle:	280
Colour Rendering Index (CRI):	80
Compatible Dimmers:	Varilight JQP401W
Instant on (Less than 1 second):	Yes
LED Type:	Surface mounted device (SMD)
Lifetime (hours):	15000
Switching Cycles:	7500

Environment

EN:	EN-62560
LVD Certified:	Yes
CE RoHS:	Yes
Energy Rating:	A+
New Energy Rating:	F
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	40

Packaging

Package Weight (g):	96
Package Length (mm):	120
Package Width (mm):	41
Package Depth (mm):	41
Qty per euro pallet:	2400