
## Vision 3 LED

## Supplied c/w Integral Driver and 3 Trim Designs

- IP65 polycarbonate 3-In-1 LED luminaire for external applications
- Each fitting supplied with plain, louvred eyelid and plain eyelid covers
- Exceeds performance of CFL equivalents
- Integral die-cast aluminium heatsink provides thermally managed high performance
- 20W LED lifespan L70 56,000 hours
- Non-dimmable





## **LED** Information

Total (Watts)	17W
Lumens Delivered	1
Cool White	1420lm
Warm White	1324lm
Lm/W Cool White	84lm*
Lm/W Warm Whit	e 83lm*
CRI	Ra 80
CCT	4000K
	3000K
Input	230V
Hertz	50/60Hz
Operating Temp	-10°C to 50°C

<sup>\*</sup> Please note that Lm/W rating reduces for eyelid versions





Fitted with Solid Eg lid

Fitted with Louv ed Ey lid

	Code	Lamp	Description
Standard	AVILED/CCT/GR	LED	17W - Graphite - Cool White/Warm White
	AVILED/CCT/SG	LED	17W - Silver Grey - Cool White/Warm White
	AVILED/CCT/W	LED	17W - White - Cool White/Warm White
PIR	AVILED/CCT/GR/PIR	R LED	17W - Graphite - Cool White/Warm White - PIR
	AVILED/CCT/SG/PIR	R LED	17W - Silver Grey - Cool White/Warm White - PIR
	AVILED/CCT/W/PIR	LED	17W - White - Cool White/Warm White - PIR

Options	/M3	Emergency
	/MWS	Integral Microwave Sensor
	/MWS/M3	Integral Microwave Sensor Emergency

**Warrington:** +44 (0) 1942 433333 **Belfast:** +44 (0) 2890 773750

