Supplied c/w Integral Driver and 3 Trim Designs







AVIMLED/GR/PIR






AVIMLED/SG/PIR - Fitted with Louv ed Ey lid

AVIMLED/W - Fitted with Louw ed Eye lid

	Code	Lamp	Description
Standard	AVIMLED/GR	LED	9W - Graphite
	AVIMLED/SG	LED	9W - Silver Grey
	AVIMLED/W	LED	9W - White
PIR	AVIMLED/GR/PIR	LED	9W - PIR - Graphite
	AVIMLED/SG/PIR	LED	9W - PIR - Silver Grey
	AVIMLED/W/PIR	LED	9W - PIR -White

- IP65 polycarbonate LED luminaire for external applications
- Each fitting supplied with plain, louvred eyelid and plain eyelid covers
- Exceeds performance of CFL equivalents
- Integral die-cast aluminium heatsink provides thermally managed high performance
- LED lifespan L70 36,000 hours
- Non-dimmable







Max 8 metres 8 e o nds to 5 minutes 2 to 2000 LUX

LED Information

Total (Watts)	9W
Lumens Delivered	797lm
Lm/W	89lm*
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-10°C to 50°C

^{*} Please note that Lm/W rating reduces for eyelid versions





