



ATORLED5/110V/M3

Tornado 110V LED - Self-Test Emergency 28W



Features

LED Performance allows point-to-point replacement of existing fluorescent luminaires

Suitable for all types of site lighting

Light output exceeds performance of T8 and T5 fluorescent

Unique luminaire fixing clip design allows option of mounting onto BESA box

IK08 Rating

Lockable heavy-duty stainless steel clips supplied as standard for added safety and security

Self-test emergency as standard

LED lifespan L70 35,000 hours

Non-dimmable

General Information

Lamp Type	LED
Colour / Finish	Yellow
Emergency	Yes
Self Test	Yes
IP Rating	IP65
Class Protection	1
Internal / External	Internal / External
Surface / Recessed / Suspended	Surface
Warranty (Years)	3
CE Mark	Yes
Length (mm)	1566
Width (mm)	85
Height (mm)	75

Technical Information

Wattage	28W
Lumens Delivered	3230lm
Lm/W	115 Lm/W
CRI	80
CCT	4000K
Input	100/240V
Hertz	50Hz
Operating Temp	-10 to 40°C

Datasheet generated from <http://www.electrika.com> last updated Thursday, September 20, 2018 1:32:23 PM

	Code	A	B	C	D
	ATORLED4/110V	1266	860	75	85
	ATORLED5/110V	1566	960	75	85
	ATORLED2X4/110V	1266	860	75	118
	ATORLED2X5/110V	1566	960	75	118