



ATORLED5/110V

Tornado 110V LED 28W



Features

LED Performance allows point-to-point replacement of existing fluorescent luminaires

Suitable for all types of site lighting

Light output exceeds performance of T8 and T5 fluorescent

Unique luminaire fixing clip design allows option of mounting onto BESA box

IK08 Rating

Lockable heavy-duty stainless steel clips supplied as standard for added safety and security

Self-test emergency as standard

LED lifespan L70 35,000 hours

Non-dimmable

General Information

| | |
|--------------------------------|---------------------|
| Lamp Type | LED |
| Colour / Finish | Yellow |
| IP Rating | IP65 |
| Class Protection | 1 |
| Internal / External | Internal / External |
| Surface / Recessed / Suspended | Surface |
| Warranty (Years) | 3 |
| CE Mark | Yes |
| Length (mm) | 1566 |
| Width (mm) | 85 |
| Height (mm) | 75 |

Technical Information

| | |
|------------------|-------------|
| Wattage | 28W |
| Lumens Delivered | 3230lm |
| Lm/W | 115 Lm/W |
| CRI | 80 |
| CCT | 4000K |
| Input | 100/240V |
| Hertz | 50Hz |
| Operating Temp | -10 to 40°C |

Datasheet generated from <http://www.electrika.com> last updated Thursday, September 20, 2018 1:32:23 PM

| | Code | A | B | C | D |
|--|------------------------|------|-----|----|-----|
| | ATORLED4/110V | 1266 | 860 | 75 | 85 |
| | ATORLED5/110V | 1566 | 960 | 75 | 85 |
| | ATORLED2X4/110V | 1266 | 860 | 75 | 118 |
| | ATORLED2X5/110V | 1566 | 960 | 75 | 118 |