

Slim-Fit™

Low Profile Aluminium Downlights

Edge-lit low profile ideal for installations with limited recess space (20mm for downlight, 40mm space for driver)

IP44 rated

Opal diffuser for even light distribution

Supplied with remote non-dimmable constant current driver



Ultra slim 20mm profile, ideal for shallow ceiling voids



Cat. No.	Watts	Colour	Lumens	lm/W	Beam	Cut-out [Ø]	Triac Dimmable Drivers (sold separately)
Non-Dimmable							
EN-PL06C*/30	6W	3000K	480lm	80	120°	108mm	
EN-PL06C*/40	6W	4000K	530lm	88	120°	108mm	EN-PLDD06C
EN-PL06C*/65	6W	6500K	500lm	83	120°	108mm	
EN-PL09C*/30	9W	3000K	810lm	90	120°	135mm	
EN-PL09C*/40	9W	4000K	900lm	100	120°	135mm	EN-PLDD12C
EN-PL09C*/65	9W	6500K	855lm	95	120°	135mm	
EN-PL12C*/30	12W	3000K	1120lm	93	120°	157mm	
EN-PL12C*/40	12W	4000K	1200lm	100	120°	157mm	EN-PLDD12C
EN-PL12C*/65	12W	6500K	1150lm	96	120°	157mm	
EN-PL18C*/30	18W	3000K	1710lm	95	120°	206mm	
EN-PL18C*/40	18W	4000K	1890lm	105	120°	206mm	EN-PLDD18C
EN-PL18C*/65	18W	6500K	1800lm	100	120°	206mm	
EN-PL24C*/30	24W	3000K	2280lm	95	120°	280mm	
EN-PL24C*/40	24W	4000K	2520lm	105	120°	280mm	EN-PLDD24C
EN-PL24C*/65	24W	6500K	2400lm	100	120°	280mm	

Emergency Pack

- [EN-DLEM3](#) 3 Hour Maintained Emergency Pack
- [AU-EM1EXST](#) 3 Hour Maintained Self Test Emergency Pack

*Add suffix **DA** for DALI or **V** for 1-10V dimmable option (note DALI Emergency - the EM side will not report back)



Excluding 6W

5 Year Warranty



L70 40,000hrs

1-10V, DALI and Triac dimmable options

Emergency option

Matt White finish

EN-PL18C



- [EN-PL06C](#)
(H) 20mm Height
(OD) 120mm Overall (Ø)
- [EN-PL09C](#)
(H) 20mm Height
(OD) 150mm Overall (Ø)
- [EN-PL12C](#)
(H) 20mm Height
(OD) 170mm Overall (Ø)
- [EN-PL18C](#)
(H) 20mm Height
(OD) 225mm Overall (Ø)
- [EN-PL24C](#)
(H) 20mm Height
(OD) 300mm Overall (Ø)