



## Fire Rated Downlights

- Loop in loop out terminal block for quick and easy installation
- Pressed steel body with aluminium bezel
- Insulation coverable - with LED lamps only
- Patented fire rated downlight with intumescent
- Fire, acoustic and air leakage rated
- Tested in 30, 60 and 90 minute solid timber joist, plus 30 minute i-joist and metal web joist

# LITE Range

3 Year Warranty

White, Polished Chrome & Satin Nickel finish options



### Smart Lamps

**Bluetooth**  
Lamp option  
See pg.181



### Pro/Lite Lamps

**ICE™**  
Lamp options  
See pg.57

**ClearVu™**  
Lamp options  
See pg.58

See luminaire lamp compatibility on pg.198



Fixed



Adjustable



Fixed IP65




Air leakage  
(excluding  
adjustable)

Cat. No.	Input	Horz. Adj.	Cutout (Ø)
<b>Fixed</b>			
<b>EN-FD101W</b>	240V	-	75mm
<b>EN-FD101PC</b>	240V	-	75mm
<b>EN-FD101SN</b>	240V	-	75mm
<b>Adjustable</b>			
<b>EN-FD102W</b>	240V	28°	90mm
<b>EN-FD102PC</b>	240V	28°	90mm
<b>EN-FD102SN</b>	240V	28°	90mm
<b>IP65</b>			
<b>EN-FD103W</b>	240V	-	75mm
<b>EN-FD103PC</b>	240V	-	75mm
<b>EN-FD103SN</b>	240V	-	75mm



Connector with  
push-fit loop in/loop  
out terminals suitable  
for use with solid or  
stranded cable



- EN-FD101**  
(H) 125mm Height  
(OD) 87mm Overall (Ø)
- EN-FD102**  
(H) 130mm Height  
(OD) 100mm Overall (Ø)
- EN-FD103**  
(H) 130mm Height  
(OD) 87mm Overall (Ø)

