

Vela™

Aluminium IP65 Floodlights

- Aluminium housing for excellent heat dissipation
- Tempered frosted glass
- IP65 rated
- IK06 rated (20-50W versions)
- IK05 rated (10W version)
- Pre-wired with 800mm of cable
- Salt spray tested and approved for use in coastal areas

LITE Range

3 Year Warranty

L70 30,000hrs

Black finish



LITE Range

Floodlights



Mounting bracket and cable entry

EN-FLV20



EN-FLV10

- (H) 70mm Height
- (W) 90mm Width
- (D) 24mm Depth
- (BL) 64mm Bracket Length
- (BW) 95mm Bracket Width

EN-FLV20

- (H) 88mm Height
- (W) 121mm Width
- (D) 25mm Depth
- (BL) 73mm Bracket Length
- (BW) 125mm Bracket Width

EN-FLV30

- (H) 118mm Height
- (W) 160mm Width
- (D) 25mm Depth
- (BL) 91mm Bracket Length
- (BW) 166mm Bracket Width

EN-FLV50

- (H) 143mm Height
- (W) 196mm Width
- (D) 29mm Depth
- (BL) 115mm Bracket Length
- (BW) 202mm Bracket Width

Cat. No.	Watts	Colour	Lumens	lm/W
Non-Dimmable				
EN-FLV10/40	10W	4000K	1150lm	115
EN-FLV20/40	20W	4000K	2400lm	120
EN-FLV30/40	30W	4000K	3450lm	115
EN-FLV50/40	50W	4000K	6000lm	120

