

3 Year Warranty

L70 30,000hrs

PIR sensing as standard

Black finish

VelaPIR™

Aluminium IP65 PIR Floodlight

Aluminium housing for excellent heat dissipation

Tempered frosted glass

Floodlight & PIR IP65 rated

IK06 rated (20-50W versions)

IK05 rated (10W version)

PIR 140° detection beam range up to 10m

Pre-wired with 800mm of cable

Manual override function



Salt spray tested and approved for use in coastal areas

**COMING
SPRING
2023**

PIR NOW IP65



EN-FLV10P



EN-FLV10P

- (H) 70mm Height
- (W) 90mm Width
- (D) 24mm Depth
- (BL) 120mm Bracket Length
- (BW) 95mm Bracket Width

EN-FLV20P

- (H) 88mm Height
- (W) 121mm Width
- (D) 25mm Depth
- (BL) 130mm Bracket Length
- (BW) 125mm Bracket Width

EN-FLV30P

- (H) 118mm Height
- (W) 160mm Width
- (D) 25mm Depth
- (BL) 148mm Bracket Length
- (BW) 166mm Bracket Width

EN-FLV50P


- (H) 143mm Height
- (W) 196mm Width
- (D) 29mm Depth
- (BL) 155mm Bracket Length
- (BW) 202mm Bracket Width



IP65 PIR



PIR controls



PIR sensor
detection range

Cat. No.	Watts	Colour	Lumens	lm/W
Non-Dimmable				
EN-FLV10P/40	10W	4000K	950lm	95
EN-FLV20P/40	20W	4000K	1900lm	95
EN-FLV30P/40	30W	4000K	3000lm	100
EN-FLV50P/40	50W	4000K	5000lm	100

