


# Disconnect Terminals

## ERTD2

Width: 8 mm



64.20

45.00  
MR 35 x 7.5

## ERTD4

Width: 6.2 mm



54.10

50.50  
MR 35 x 7.5

6 mm<sup>2</sup> Disconnect Terminal Block with Busbar  
For 35 mm G and DIN Rail

4 mm<sup>2</sup> Knife Disconnect Terminal Block  
For 35 mm DIN Rail



Electrical Ratings
CE (EN 60947-7-1)
cRUus
VDE (IEC 60947-7-1)
CSA
IECEX

Voltage, V ~	Current, A	Cross Section
500	6.3	6 mm <sup>2</sup>
300	6.3	AWG 26 - 8

Voltage, V ~	Current, A	Cross Section
500	16	4 mm <sup>2</sup>
600	16	AWG 26 - 10

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 Conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)
AWG Conductor
Insulation Stripping Length
Torque (min.-max.)
Screwdriver

0.2 - 10 mm <sup>2</sup>
0.2 - 10 mm <sup>2</sup>
0.5 - 4 mm <sup>2</sup>
AWG 24 - 8
10 - 12 mm
0.8 - 1.2 Nm
0.6 x 3.5


0.2 - 6 mm <sup>2</sup>
0.2 - 6 mm <sup>2</sup>
0.5 - 2.5 mm <sup>2</sup>
AWG 24 - 10
9 - 10 mm
0.5 - 0.8 Nm
0.6 x 3.5

Technical Data
Rated Impulse Voltage
Insulation material group /
Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type

6/3
1/B5
IP 20/ -

6/3
1/A4
IP 20/ -

Ordering Data
Beige
Grey



Terminal	Qty.	End Plate	Qty.
ERTD2BEIGE	25	EPF2BEIGE	25
ERTD2GREY	25	EPF2GREY	25

Terminal	Qty.	End Plate	Qty.
ERTD4BEIGE	50	EPF3BEIGE	10
ERTD4GREY	50	EPF3GREY	10

Cross Connection - Comb Connection


Part Number	Qty.	Part Number	Qty.

Part Number	Qty.	Part Number	Qty.
CCS4/2	25		
CCS4/3	20		
CCS4/4	15		

End Bracket
xx: Beige or Grey



Part Number	Qty.	Part Number	Qty.
ES1xx	100		
ES4xx	100		
ES7xx	50		
ES3xx	100		

Part Number	Qty.	Part Number	Qty.
ES1xx	100		
ES4xx	100		
ES7xx	50		

Test Plug and Sockets


Part Number	Qty.	Part Number	Qty.

Part Number	Qty.	Part Number	Qty.

Warning Label
Available in White and Yellow


With Symbol	Qty.	Without Symbol	Qty.

With Symbol	Qty.	Without Symbol	Qty.

Group Marking


Part Number	Qty.	Part Number	Qty.
GM	50	GM3	50
GM1-1	25		
GM1-2	25		
GM2-2	25		

Part Number	Qty.	Part Number	Qty.
GM	50	GM3	50
GM1-1	25		
GM1-2	25		
GM2-2	25		

Unprinted Markers



Part Number	Qty.	Part Number	Qty.
DG10/8	260		

Part Number	Qty.	Part Number	Qty.
DG10/6	360		


# Fuse Terminals

## ERF2

Width: 8 mm



64.20



45.00  
MPR 35 x 7.5

## ERF2LD

Width: 8 mm



64.20

45.00  
MPR 35 x 7.5

6 mm<sup>2</sup> Fuse Terminal Block  
For 35 mm G and DIN Rail

6 mm<sup>2</sup> Fuse Terminal Block with LED  
XX: 24AC/DC, 48AC/DC, 110AC/DC, 220AC/DC  
For 35 mm G and DIN Rail



Electrical Ratings
CE (EN 60947-7-3)
cRUus
VDE (IEC 60947-7-1)
CSA
IECEX

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 Conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)
AWG Conductor
Insulation Stripping Length
Torque (min.-max.)
Screwdriver

Technical Data
Rated Impulse Voltage
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type
Fuse Type

Ordering Data
<div style="display: flex; align-items: center;"> <div style="width: 15px; height: 10px; background-color: #c0c0c0; margin-right: 5px;"></div> Beige                 </div> <div style="display: flex; align-items: center; margin-top: 5px;"> <div style="width: 15px; height: 10px; background-color: #808080; margin-right: 5px;"></div> Grey                 </div>

Partition Plate
xx: available in all colours

Cross Connection - Comb Connection

Cross Connection - Extraction Tool

End Bracket
xx: Beige or Grey

Test Plug and Sockets

Warning Label
Available in White and Yellow

Group Marking

Unprinted Markers

Voltage, V ~	Current, A	Cross Section
500	6.3	6 mm <sup>2</sup>
300	6.3	AWG 26 - 8

0.2 - 10 mm <sup>2</sup>
0.2 - 10 mm <sup>2</sup>
0.5 - 4 mm <sup>2</sup>
AWG 24 - 8
10 - 12 mm
0.8 - 1.2 Nm
0.6 x 3.5

6/3
1/B5
IP 20/ -
G/5 x 20 - 5 x 25

Terminal	Qty.	End Plate	Qty.
ERF2BEIGE	50	EPF2BEIGE	25
ERF2GREY	50	EPF2GREY	25

Partition	Qty.	Partition	Qty.

Part Number	Qty.	Part Number	Qty.

Part Number	Qty.	Part Number	Qty.

Part Number	Qty.	Part Number	Qty.
ES1xx	100		
ES4xx	100		
ES7xx	50		
ES3xx	100		

Part Number	Qty.	Part Number	Qty.

With Symbol	Qty.	Without Symbol	Qty.

Part Number	Qty.	Part Number	Qty.
GM	50	GM3	50
GM1-1	25		
GM1-2	25		
GM2-2	25		

Part Number	Qty.	Part Number	Qty.
DG10/8	260		

Voltage, V ~	Current, A	Cross Section
	6.3	6 mm <sup>2</sup>
	6.3	AWG 26 - 8

0.2 - 10 mm <sup>2</sup>
0.2 - 10 mm <sup>2</sup>
0.5 - 4 mm <sup>2</sup>
AWG 24 - 8
10 - 12 mm
0.8 - 1.2 Nm
0.6 x 3.5

6/3
1/B5
IP 20/ -
G/5 x 20 - 5 x 25

Terminal	Qty.	End Plate	Qty.
ERF2LDXXBEIGE	25	EPF2BEIGE	25
ERF2LDXXGREY	25	EPF2GREY	25

Partition	Qty.	Partition	Qty.

Part Number	Qty.	Part Number	Qty.

Part Number	Qty.	Part Number	Qty.

Part Number	Qty.	Part Number	Qty.
ES1xx	100		
ES4xx	100		
ES7xx	50		

Part Number	Qty.	Part Number	Qty.

With Symbol	Qty.	Without Symbol	Qty.

Part Number	Qty.	Part Number	Qty.
GM	50	GM3	50
GM1-1	25		
GM1-2	25		
GM2-2	25		

Part Number	Qty.	Part Number	Qty.
DG10/8	260		