

# QWCd Slimline

Quantum, the world's most advanced direct-electric hot water cylinder

## Controls

Electronic thermostatic control with internet-connected smartphone app connectivity for remote operation (a DimplexHub is required)

## Safety Features

- Manual reset thermal cut-out
- Legionella purge

## Colour/Finish

Black.

## Element

1 ¾" M BSP 3kW immersion and boost element.

## Supply

1/N/PE 230-240V, 50Hz (Peak/Off Peak).


## Guarantee

- Inner cylinder - 25 year UK manufacturer Guarantee on parts and labour
- Immersion heaters - 2 year UK manufacturer Guarantee (excluding the effects of limescale)
- Other components - 2 year UK manufacturer Guarantee (excluding the effects of limescale)

## IP Rating

IPX1

## Product Dimensions



**Dimplex Control**  
See page 10  
for details

Model	Capacity (L)	Height (mm)	Diameter (mm)	Weight (kg)	Reheat (mins)
QWCd135-480RF	135	1387	480	22	132
QWCd180-480RF	180	1761	480	30	200

# ECsd Direct Water Cylinder

EC Unvented Stainless Steel Direct Hot Water Cylinders

## Controls

Mechanical thermostat control.

## Safety Features

Manual reset thermal cut-out.

## Colour/Finish

Black.

## Element

Electronic thermostat control.

## Supply

1 ¾" M BSP 3kW immersion and boost element.


## Guarantee

- Inner cylinder - 25 year UK manufacturer Guarantee on parts and labour
- Immersion heaters - 2 year UK manufacturer Guarantee (excluding the effects of limescale)
- Other components - 2 year UK manufacturer Guarantee

## IP Rating

IPX1

## Product Dimensions



Model	Capacity (L)	Height (mm)	Diameter (mm)	Weight (kg)	Reheat (mins)
ECsd100-580	100	795	580	20	88
ECsd125-580	125	945	580	23	122
ECsd150-580	150	1115	580	27	150
ECsd175-580	175	1265	580	29	170
ECsd210-580	210	1490	580	34	218
ECsd250-580	250	1765	580	42	284
ECsd300-580	300	2065	580	48	313