


DATASHEET



TORCW2

230V IP65 IK08 2ft Selectable 14W/26W CCT Adjustable Non-Corrosive

www.mlaccessories.co.uk



MLA PART CODE	TORCW2
DESCRIPTION	230V IP65 IK08 2ft Selectable 14W/26W CCT Adjustable Non-Corrosive
NET WEIGHT (KG)	1.16
FINISH	Grey
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 653 Width - 129 Projection - 90
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP65
IK RATING	IK08
WATTAGE (W)	14/26
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	1925/2100/2085, 3215/3955/3500
LUMENS LIGHT SOURCE ONLY (LM)	4465
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	169.9
CIRCUIT WATTAGE (W)	13.6/26.2
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.118
DISPLACEMENT FACTOR	>0.9
SVM	0.018
PST-LM	0.039
BEAM ANGLE (DEGREES)	130

LIFE SPAN (HRS)	50,000
L70B50 LIFESPAN (HRS)	60000
DIMMABLE	No
OPERATING TEMPERATURE	-20~40°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 15/30W OUTPUT VOLTAGE - 35-49V OUTPUT CURRENT - 300/600mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 90.2 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -20~50°C CASE TEMPERATURE (Tc) - 75°C
WARRANTY	5year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270851601

Date Created: 08/01/2024 20:17

